



## Type of luminaire

Type of luminaire	Wall luminaire.
Photometric body	Diffuse downward-directed hemispherical light
Characteristics of the luminaire	A luminaire with contemporary design. For lighting private areas and other architectural concepts.

## General information

Materials	Powder painted aluminum cast. Lens - safety glass, transparent. Silicone gasket. EPDM cable gland.
Mounting method	Fixing of the luminaire: 2 holes ø4mm, spacing 104mm.
Terminal	Connection terminals: max 3x2,5mm², possibility to connect luminaire in loop max 3x1,5mm². A round wire in the isolation with a diameter ø7...10,5mm.
Type of light source	LED module AC integrated Replaceable (LED only) light source by a professional.
Light control	Non-dimmable luminaire
Net / gross weight of luminaire	1,41kg / 1,58kg
Box dimensions [cm]	23x16x8
Luminaire dimensions [cm]	20x15x6

## Technical data

LED module	Philips Fortimo DLM ES 1100/8xx G2 3K (Ⓞ Datasheet)
Luminaire wattage	9,5W
Luminaire luminous flux	920lm
Efficiency of the luminaire	96,8lm/W
ULOR	0%
Color temperature	3000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
Rated life time L70/B50 at 25°C	50 000h
Power Factor luminaire	PF > 0,9
Ta Rated temperature	+25°C, up to +50°C on request

This product contains light source of energy efficiency class **E** / **EPREL**

Inrush current	2,98A / 34,07µs
----------------	-----------------

## Accessories sold separately, xx - color of the luminaire

151XX0009	Corner bracket for fixture mounting
-----------	-------------------------------------

## Spare parts

ZS1330zx0009	Service set.
--------------	--------------

## Files to download

Photometric LDT files	Photometric IES files
Manual	BIM ArchiCAD

## Indexes

Index	Color	RAL
1330AL	ALUMINIUM	9006
1330GR	GRAPHITE	7016
1330W	WHITE	9003



Management System  
ISO 9001:2015  
IATF 16949:2016  
www.tuv.com  
ID 9108651873

