

NORLYS TRYSIL 1060


IP 65 | IK 10 | AC 220-240V 50-60Hz | LED | DIM

Trysil1060XX0009
14.10.2026 v.09.3
www.norlys.no









Type of luminaire

Type of luminaire	Pole luminaire
Photometric body	Diffuse downward-directed hemispherical light
Characteristics of the luminaire	For lighting private areas and other architectural concepts

General information

Materials	Extruded aluminum profile, powder coated. Lens - transparent polycarbonate with structure, UV stabilized. Silicone gasket.
Mounting method	According to the attached assembly instructions. Other accessories must be purchased separately.
Terminal	Connection terminals: max 3x4mm² Possibility of connecting the luminaire in loops of max. 3x2.5mm² Round insulated cable with a maximum diameter of ø12.5 mm
Type of light source	LED module, electronic power supply Replaceable (LED only) light source by a professional. Replaceable control gear by a professional.
Light control	Phase-dimming (TRIAC) TRAILING EDGE (TE) - LEADING EDGE (LE)
Luminaire weight net / gross	19,2kg / 21,4kg
Box dimensions [cm]	44cm x 38cm x 232cm
Luminaire dimensions [cm]	71cm x 24cm x 300cm

Technical data

2 LED modules	Cree DK200305 V3 JB2835 3V 3K (Datasheet)
Driver	Yes
Driver durability	50000h
Light source wattage	15,1W
Luminaire wattage	17W
Lamp luminous flux	2748lm
Luminaire luminous flux	1667lm
Efficiency of the luminaire	98,1lm/W
ULOR	0%
Color temperature	3000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
L80TM-21 [wg LM-80]	102 000h
L90 TM-21 [wg LM-80]	52 600h
Power Factor luminaire	PF 0,85
THD factor	10%
Ta Rated temperature	+25°C
Ambient operating temp. range	-20...+45°C

This product contains light sources of energy efficiency class C / EPREL

Optional luminaire also available:
- Operating mode/dimming: 1...10V
- In a safety class for KL II
- For LED color 2700K
- For a different luminous flux value
- Version with surge protection device (SPD)
- For a different color of the fixture (according to the RAL color palette)
- For a different frame height

Terms of sale and other information, after contact with the Norlys Sales Department.

Inrush current	5A / 50µs
BUG rating	B1-U1-G1

Spare parts

ZS1084zx0009	Repair kit.

Files to download

Photometric LDT files	Photometric IES files
Manual	

Norlys AS
P.B 1014 Hoff, 0218
Oslo
Hovfaret 4B, 0275
Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no

TÜVRheinland CERTIFIED — Management System ISO 9001:2015 IATF 16949:2016 — www.tuv.com ID 9108651873

PCC cert CERTIFICATE ISO 14001

RoHS 2011/65/UE

Before the installation, please read the instructions included with the luminaire. Installation and service work are carried out by a person with appropriate authorizations and qualifications, in accordance with applicable regulations. Due to the dynamic development of lighting technology, we provide additional information upon customer request. Condensation that may occur in luminaires is a natural phenomenon and does not affect the quality of the luminaire.

TRYSIL 1060

Indexes

Index	Color	RAL
1060AL	ALUMINUM	9006
1060BL	BLACK	9005
1060GR	GRAPHITE	7016

Other colors according to the "Colors Template" / RAL pattern book - available on request, subject to agreement with Norlys' Sales Department.

Norlys AS
P.B 1014 Hoff, 0218
Oslo
Hovfaret 4B, 0275
Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no

Before the installation, please read the instructions included with the luminaire. Installation and service work are carried out by a person with appropriate authorizations and qualifications, in accordance with applicable regulations. Due to the dynamic development of lighting technology, we provide additional information upon customer request. Condensation that may occur in luminaires is a natural phenomenon and does not affect the quality of the luminaire.