



Type of luminaire	
Type of luminaire	Post light fixture.
Photometric body	Indirect light with rotationally symmetrical light distribution facing down.
Characteristics of the luminaire	Bollard luminaire of stable and durable construction. For lighting private areas and public spaces.

General information	
Materials	Powder painted aluminum cast. Lens - clear polycarbonate, UV stabilized. Silicone gasket. Nylon6 cable gland.
Mounting method	Fixing of the luminaire: 3 holes ø9mm with a diameter of ø145mm every 120°. The luminaire is equipped with TH-35 rail with a length of 100mm.
Terminal	Connection terminals: max 3x2,5mm <sup>2</sup> , possibility to connect luminaire in loop max 3x2,5mm <sup>2</sup> . A round wire in the isolation with a diameter of ø8...17mm.
Type of light source	LED module, electronic power supply Replaceable (LED only) light source by a professional. Replaceable control gear by a professional.
Light control	Non-dimmable fixture
Luminaire weight net	11,03kg
Box dimensions [cm]	22,5cm x 22,5cm x 103,5cm

Technical data	
LED module	Yes
Light source wattage	14,7W
Luminaire wattage	17,5W
Lamp luminous flux	1380lm
Luminaire luminous flux	559lm
Efficiency of the luminaire	31,9lm/W
Color temperature	3000K
Colour rendering index CRI	80
Power Factor luminaire	PF 0,49
Ta Rated temperature	+25°C
Ambient operating temp. range	-20...+45°C
Inrush current	50A/190µs

Maximum number of luminaires of this type per MCB:  
B 10A: 8, B 16A: 14

Accessories <small>sold separately</small>	
1231GA0009	Ground anchor
3087GA0009	Mounting adapter
1230ZX0009	Concreting anchor
1232GA0010	Adapter for concrete foundation

Spare parts	
0925920130	LED module.
46999706	Power supply.

Indexes		
Index	Color	RAL
1240 KL IIAL	ALUMINUM	9006
1240 KL IIGR	GRAPHITE	7016

Other colors according to the "Colors Template" pattern book - available on request, subject to agreement with Norlys' Sales Department.