



Type of luminaire

Type of luminaire	Post light fixture.
Photometric body	Indirect light with rotationally symmetrical light distribution facing down.
Characteristics of the luminaire	Bollard luminaire of stable and durable construction. For lighting private areas and public spaces.

General information

Materials	Powder painted aluminum cast. Lens - clear polycarbonate, UV stabilized. Silicone gasket. Nylon6 cable gland.
Mounting method	Fixing of the luminaire: 3 holes $\varnothing 9\text{mm}$ with a diameter of $\varnothing 145\text{mm}$ every 120°. The luminaire is equipped with TH-35 rail with a length of 100mm.
Terminal	Connection terminals: max $3 \times 2,5\text{mm}^2$, possibility to connect luminaire in loop max $3 \times 2,5\text{mm}^2$. A round wire in the isolation with a diameter of $\varnothing 8...17\text{mm}$.
Type of light source	LED module, electronic power supply Replaceable (LED only) light source by a professional. Replaceable control gear by a professional.
Light control	Non-dimmable fixture
Net weight of luminaire	11,03kg
Box dimensions [cm]	22,5x22,5x103,5

Technical data

Luminaire wattage	17,5W
Luminaire luminous flux	559lm
Efficiency of the luminaire	31,9lm/W
Color temperature	3000K
Colour rendering index CRI	80
Rated life time L70/B50 at 25°C	50 000h
Power Factor luminaire	PF 0,49
Ta Rated temperature	+25°C, up to +50°C on request
Ambient temperature	Ta max=+65°C
Inrush current	50A/190 μs

Maximum number of luminaires of this type per MCB:

B 10A: 8, B 16A: 14

Accessories sold separately

1230ZX0009	Concreting anchor.
1231GA0009	Ground anchor.
1232GA0009	Anchoring support.

Spare parts

0925920130	LED module.
46999706	Power supply.

Indexes

Index	Color	RAL
1240 KL IIAL	ALUMINUM	9006
1240 KL IIGR	GRAPHITE	7016