


NORLYS ASKER POLE PRO 1367


AC 220-240V 50-60Hz | IP 65 | IK 06 | LED | No Dim

Asker pole pro
1367XX0010
02.11.2026 v.10.11
www.norlys.no









Type of luminaire

Type of luminaire	Pole luminaire (light construction).
Photometric body	Ledil lens type T2-L (IESNA type III)
Characteristics of the luminaire	For the lighting of private areas, parks, and other architectural concepts.

General information

Materials	Extruded aluminum profile, powder coated. The outer hermetic lens - transparent PMMA plastic Silicone gasket.
Mounting method	Fixture mounting: 4 holes ø12mm, spacing 200x200mm. According to the attached installation instructions. Other accessories must be purchased separately.
Terminal	Connection terminals: max 3x4mm², possibility to connect the fixture in a loop max 3x4mm² Cable in a round casing with a diameter: ø4...8mm, ø8...12mm or ø10...13.6mm
Type of light source	Optical kit with IP67 (LED module and lens); electronic power supply Replaceable (LED only) light source by a professional. Replaceable control gear by a professional.
Light control	Non-dimmable fixture
Luminaire weight net / gross	11kg / 17,05kg
Box dimensions [cm]	26cm x 240cm x 53cm
Luminaire dimensions [cm]	236cm x 11cm x 39cm
Side area of luminaire	0,258m²

Technical data

LED module	Philips Fortimo FastFlex LED 2x6 DP G5 3K (Datasheet)
Driver	Yes
Driver durability	50000h
Light source wattage	6,1W
Luminaire wattage	7,9W
Lamp luminous flux	1158lm
Luminaire luminous flux	1125lm
Luminous intensity of the luminaire	1055cd
Efficiency of the luminaire	142,4lm/W
ULOR	0,86%
Color temperature	3000K
Colour consistency (McAdam ellipse)	SDCM5
Flicker of light (Pst LM)	≤1
Strobe effect (SVM)	≤0.4
Colour rendering index CRI	70
L90B10 [wg LM-80]	>100 000h
Power Factor luminaire	PF 0,86
THD factor	< 15%
Ta Rated temperature	+25°C
Ambient operating temp. range	-20...+45°C
This product contains light source of energy efficiency class D / EPREL	
Inrush current	5A / 50µs
BUG rating	B1-U2-G1

Maximum number of luminaires of this type per MCB:

B 10A: 31, B 16A: 50, C 10A: 52, C 16A: 85

Accessories sold separately

116ZX0009	Concreting anchor
117GA0009	Ground anchor

Spare parts

ZS1367xx0010	Repair kit.

Norlys AS
P.B 1014 Hoff, 0218
Oslo
Hovfaret 4B, 0275
Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no

TÜVRheinland CERTIFIED — Management System ISO 9001:2015 IATF 16949:2016 — www.tuv.com ID 9108651873

PCC Cert CERTIFICATE ISO 14001

RoHS 2011/65/UE

ASKER POLE PRO 1367

Files to download

Photometric LDT files	Photometric IES files
Manual	

Indexes

Index	Color	RAL
1367AL	ALUMINUM	9006
1367BL	BLACK	9005
1367GR	GRAPHITE	7016

Other colors according to the "Colors Template" / RAL pattern book - available on request, subject to agreement with Norlys' Sales Department.

Norlys AS
P.B 1014 Hoff, 0218
Oslo
Hovfaret 4B, 0275
Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no