


NORLYS ASKER POLE PRO 1368


IP 65 | IK 08 | AC 220-240V 50-60Hz | LED | DALI2

Asker pole pro
1368XX0009
16.09.2026 v.09.19
www.norlys.no









Type of luminaire

Type of luminaire	Pole luminaire (light construction).
Photometric body	Ledil lens type T2-L (IESNA type III)
Characteristics of the luminaire	For lighting private areas, parks, and other architectural concepts. The wide and even light beam is perfect for illuminating paths, walkways, etc. Light and connection chamber sealing IP65.

General information

Materials	Extruded aluminum profile, powder coated. The outer hermetic lens - transparent PMMA plastic Silicone gasket.
Mounting method	Mounting of the luminaire: 4 holes ø12mm, spacing 200x200mm, Other accessories must be purchased separately
Terminal	Connection terminals: max 5x4mm², Possibility to connect the luminaire in loops max 5x4mm², Round insulated cable with a maximum diameter of ø12,5mm
Type of light source	LED module, DALI outdoor electronic power supply Replaceable (LED only) light source by a professional. Replaceable control gear by a professional.
Light control	System light control: DALI outdoor full programm. The power supply is programmed for the maximum permitted current. Programming of other parameters after contact with the Norlys Sales Department.
Luminaire weight net / gross	10,54kg / 12,11kg
Box dimensions [cm]	25cm x 115cm x 56cm
Luminaire dimensions [cm]	390cm x 24cm x 216cm
Side area of luminaire	0,232m²

Technical data

LED module	Philips Fortimo FastFlex LED 2x6 DP G5 3K (Datasheet)
Driver	Yes
Driver durability	100000h
External control	DALI2 / NightDim (XI FP NLD) (User manual)
Light source wattage	6,4W
Luminaire wattage	8,6W
Lamp luminous flux	1158lm
Luminaire luminous flux	1130lm
Luminous intensity of the luminaire	1006cd
Efficiency of the luminaire	131,4lm/W
ULOR	0,87%
Color temperature	3000K
Colour consistency (McAdam ellipse)	SDCM4
Colour rendering index CRI	70
L90B10 [wg LM-80]	>100 000h
Ta Rated temperature	+25°C
Ambient operating temp. range	-20...+45°C

This product contains light source of energy efficiency class D / EPREL

Maximum number of luminaires of this type per MCB:

B 16A: 29, C 10A: 30, C 16A: 43

Accessories sold separately

117GA0009	Ground anchor
116ZX0009	Concreting anchor

Spare parts

ZS1368zx0009	Service set.

Files to download

Photometric LDT files	Photometric IES files
Manual	BIM Revit
BIM ArchiCAD	

Norlys AS
P.B 1014 Hoff, 0218
Oslo
Hovfaret 4B, 0275
Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no

TÜVRheinland CERTIFIED — Management System ISO 9001:2015 IATF 16949:2016 — www.tuv.com ID 9108651873

PCC Cert CERTIFICATE ISO 14001

RoHS 2011/65/UE

Before the installation, read the instructions attached to the luminaire. Due to the dynamic development of lighting technology, we provide additional information at the client's request. LED module replaceable by a person with appropriate qualifications, following applicable regulations. Condensation, which may occur in luminaires, is a natural phenomenon and does not deteriorate the quality of the luminaire

ASKER POLE PRO 1368

Indexes

Index	Color	RAL
1368AL	ALUMINUM	9006
1368BL	BLACK	9005
1368GR	GRAPHITE	7016

Other colors according to the "Colors Template" pattern book - available on request, subject to agreement with Norlys' Sales Department.

Norlys AS
P.B 1014 Hoff, 0218
Oslo
Hovfaret 4B, 0275
Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no

Before the installation, read the instructions attached to the luminaire. Due to the dynamic development of lighting technology, we provide additional information at the client's request. LED module replaceable by a person with appropriate qualifications, following applicable regulations. Condensation, which may occur in luminaires, is a natural phenomenon and does not deteriorate the quality of the luminaire