



Type of luminaire

Type of luminaire	Post light fixture.
Photometric body	Rotationally symmetric light shaded from above.
Characteristics of the luminaire	Bollard fixture with a stable and durable construction. For lighting private areas and public zones.

General information

Materials	Wood - scandinavian impregnated pine and hot-dip galvanized steel. Wood - scandinavian impregnated pine, hot-dip galvanized and powder painted steel. Lens - plastic PMMA in milky color. Silicone gasket.
Mounting method	Fixture mounting: 3 holes ø9mm, on a ø65mm diameter 120° apart.
Terminal	Connection terminals: max 3x2.5mm ² , possibility of connecting the fixture in a loop max 3x1.5mm ² . Cable in a round sheath with a maximum diameter of ø12.5mm.
Type of light source	Lamp E27 Replaceable light source by an end-user.
Luminaire weight net / gross	5,9kg / 7,3kg
Box dimensions [cm]	20,5cm x 20,5cm x 91cm
Luminaire dimensions [cm]	15cm x 15cm x 85cm

Technical data

Lamp E27	Yes
Light source wattage	LED max 9W
Luminaire wattage	LED max 9W
ULOR	11%
Ta Rated temperature	+25°C
Ambient operating temp. range	TA MAX=+65°C

Optional version, deadline, and terms of execution upon agreement with Norlys Sp. z o.o. Sales Department. Possibility to order a fixture with a Philips Master LEDbulb E27 type 806lm/8.5W/2700K (dimmable) LED lamp.

BUG rating	B0-U1-G0
------------	----------

Accessories sold separately

3086GA0009	Mounting adapter
3080GA0009	Mounting adapter
206GA0010	Ground anchor
206GA0S10	Adapter for concrete foundation
205ZX0010	Concreting anchor

Recommended light sources

Osram LED Parathom Classic E27	Philips Master LEDbulb / Ledbulb Classic E27
Osram ECO PRO Classic 46 <=> 60W E27	Philips ECO Classic 42 <=> 60W E27

Spare parts

06291001	Lampshade - service kit
08288004	Gasket.

Files to download

Photometric LDT files	Photometric IES files
3D models and drawings	Manual
BIM ArchiCAD	

Indexes

Index	Color	RAL
1443BL	BLACK	9005
1443GA	HOT-DIP GALVANIZING	-

Other colors according to the "Colors Template" pattern book - available on request, subject to agreement with Norlys' Sales Department.