



Type of luminaire

Type of luminaire	Post light fixture.
Photometric body	Rotationally symmetric light shaded from above.
Characteristics of the luminaire	Bollard luminaire of stable and durable construction. For lighting private areas and public spaces.

General information

Materials	Hot-dip galvanized steel. Lens - plastic PMMA in milky color. Silicone gasket.
Mounting method	Fixing of the luminaire: 3 holes \varnothing 9mm with a diameter of \varnothing 65mm every 120°.
Terminal	Connection terminals: max 3x4mm ² , possibility to connect luminaire in loop max 3x2,5mm ² . A round wire in the isolation with a diameter of max \varnothing 12,5mm.
Type of light source	LED E27 lamp
Light control	Phase-dimming (TRIAC) TRAILING EDGE (TE) - LEADING EDGE (LE)
Luminaire weight net / gross	9,05kg / 10,5kg
Box dimensions [cm]	20,5cm x 20,5cm x 91cm

Technical data

Light source wattage	8,5W
Luminaire wattage	8,5W
Lamp luminous flux	806lm
Luminaire luminous flux	132lm
Efficiency of the luminaire	15,5lm/W
Color temperature	2700K
Colour consistency (McAdam ellipse)	SDCM6
Colour rendering index CRI	80
L70B50 [wg LM-80]	>25 000h
Power Factor luminaire	PF 0,70
Ta Rated temperature	+25°C
Ambient operating temp. range	Ta max=+65°C

This product contains light source of energy efficiency class **F**

Accessories sold separately

3086GA0009	Mounting adapter
3080GA0009	Mounting adapter
206GA0010	Ground anchor
206GA0S10	Adapter for concrete foundation
205ZX0010	Concreting anchor

Recommended light sources

Osram LED Parathom Classic E27 Philips Master LEDbulb / Ledbulb Classic E27

Spare parts

06291001	Lampshade - service kit
08288004	Gasket.
46999021	LED E27 lamp

Files to download

Photometric LDT files	Photometric IES files
3D models and drawings	Manual

Indexes

Index	Color	RAL
1475BL	BLACK	9005
1475GA	HOT-DIP GALVANIZING	-

Other colors according to the "Colors Template" pattern book - available on request, subject to agreement with Norlys' Sales Department.