



Type of luminaire	
Type of luminaire	Post light fixture.
Photometric body	Rotationally symmetric light shaded from above.
Characteristics of the luminaire	Bollard luminaire of stable and durable construction. For lighting private areas and public spaces.

General information	
Materials	Hot-dip galvanized steel. Lens - plastic PMMA in milky color. Silicone gasket.
Mounting method	Fixing of the luminaire: 3 holes ø9mm with a diameter of ø65mm every 120°.
Terminal	Connection terminals: max 3x4mm ² , possibility to connect luminaire in loop max 3x2,5mm ² . A round wire in the isolation with a diameter of max ø12,5mm.
Type of light source	LED module AC integrated
Light control	Phase-dimming (TRIAC) TRAILING EDGE (TE) - LEADING EDGE (LE)
Luminaire weight net / gross	9,3kg / 10,7kg
Box dimensions [cm]	20,5cm x 20,5cm x 91cm

Technical data	
LED module	Yes
Light source wattage	10W
Luminaire wattage	10W
Lamp luminous flux	900lm
Luminaire luminous flux	136lm
Efficiency of the luminaire	13,6lm/W
Color temperature	3000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
Power Factor luminaire	PF > 0,99
Ta Rated temperature	+25°C
Ambient operating temp. range	TA MAX=+65°C
Inrush current	46,1mA/500µs
BUG rating	B0-U2-G1

Maximum number of luminaires of this type per MCB:
B 10A: 42, B 16A: 68, C 10A: 70, C 16A: 115

Accessories <small>sold separately</small>	
3086GA0009	Mounting adapter
205ZX0010	Concreting anchor
3080GA0009	Mounting adapter
206GA0010	Ground anchor
206GA0S10	Adapter for concrete foundation

Spare parts	
06291001	Lampshade - service kit
08288004	Gasket.
46999366	LED module.

Files to download	
Photometric LDT files	Photometric IES files
3D models and drawings	Manual

Indexes		
Index	Color	RAL
1479BL	BLACK	9005
1479GA	HOT-DIP GALVANIZING	-

Other colors according to the "Colors Template" pattern book - available on request, subject to agreement with Norlys' Sales Department.