



Type of luminaire

| | |
|----------------------------------|--|
| Type of luminaire | Post light fixture. |
| Photometric body | Rotationally symmetric light shaded from above. |
| Characteristics of the luminaire | A pillar fixture with a stable and durable construction. For lighting private areas and public spaces. |

General information

| | |
|------------------------------|--|
| Materials | Hot-dip galvanized steel. Lens - plastic PMMA in milky color. Silicone gasket. |
| Mounting method | Fixing of the luminaire: 3 holes $\varnothing 9$ mm with a diameter of $\varnothing 65$ mm every 120° . |
| Terminal | Connection terminals: max 3×4 mm ² , possibility to connect luminaire in loop max $3 \times 2,5$ mm ² . A round wire in the isolation with a diameter of max $\varnothing 12,5$ mm. |
| Type of light source | LED module AC integrated Replaceable (LED only) light source by a professional. |
| Light control | Phase-dimming (TRIAC) TRAILING EDGE (TE) - LEADING EDGE (LE) |
| Luminaire weight net / gross | 9,8kg / 9,8kg |
| Box dimensions [cm] | 21cm x 21cm x 57cm |

Technical data

| | |
|-------------------------------------|--------------------|
| LED module | Yes |
| Light source wattage | 10W |
| Luminaire wattage | 10W |
| Lamp luminous flux | 900lm |
| Luminaire luminous flux | 136lm |
| Efficiency of the luminaire | 13,6lm/W |
| Color temperature | 3000K |
| Colour consistency (McAdam ellipse) | SDCM3 |
| Colour rendering index CRI | 80 |
| L70B50 [wg LM-80] | >50 000h |
| Power Factor luminaire | PF > 0,99 |
| Ta Rated temperature | +25°C |
| Ambient operating temp. range | TA MAX=+65°C |
| Inrush current | 46,1mA/500 μ s |
| BUG rating | B0-U2-G1 |

Accessories sold separately

| | |
|------------|---------------------------------|
| 3086GA0009 | Mounting adapter |
| 205ZX0010 | Concreting anchor |
| 3080GA0009 | Mounting adapter |
| 206GA0010 | Ground anchor |
| 206GA0S10 | Adapter for concrete foundation |

Spare parts

| | |
|----------|-------------------------|
| 06291001 | Lampshade - service kit |
| 08288004 | Gasket. |
| 46999366 | LED module. |

Files to download

| | |
|-----------------------|-----------------------|
| Photometric LDT files | Photometric IES files |
| Manual | |

Indexes

| Index | Color | RAL |
|--------|---------------------|------|
| 1479BL | BLACK | 9005 |
| 1479GA | HOT-DIP GALVANIZING | - |

Other colors according to the "Colors Template" pattern book - available on request, subject to agreement with Norlys' Sales Department.