NORLYS ARENDAL MINI 1566 CE FILL AC DE 165 168 168


























Type of luminaire		
Type of lumianire	Post light fixture.	
Photometric body	Light discovered.	
Characteristics of the luminaire	A luminaire with a modern design, in which a combination of a decorative crystal lampshade with a durable and stable structure of the luminaire.	

Hot-dip galvanized steel. Hot-dip galvanized and powder-coated steel. Lens - crystal glass, satin inside. Lens may change to light amber colour over time.
Mounting of the luminaire: 2 holes ø 6.8mm at a distance of 38mm
Connection terminals: max 2x2.5mm² Possibility of connecting the luminaire in loops of max. 2x2.5mm² Round insulated cable with a maximum diameter of ø12.5mm
LED module AC integrated Replaceable (LED only) light source by a professional.
Phase-dimming (TRIAC) TRAILING EDGE (TE) - LEADING EDGE (LE)

Technical data		
External control	Phase dimmer Lumens LED AC (User manual)	
Luminaire wattage	4W	
Luminaire luminous flux	330lm	
Color temperature	3000K	
Colour consistency (McAdam ellipse)	SDCM3	
Colour rendering index CRI	80	
Rated life time L70/B50 at 25°C	>50 000h	
LED photobiological threat	RG0 or RG1	
Power Factor luminaire	PF>0,98	
THD factor	<20%	
Ta Rated temperature	+25°C, up to +50°C on request	
Ambient temperature	Ta max=+65°C	
This product contains light source of energy efficiency class $\widehat{\mathbb{C}}$ PPREL		
Inrush current	17mA / 60ms	

IIIIusiiculielit	I/IIIA/ OUTIS		
BUG rating	B0-U3-G0		
Accessories sold separately			
204GA0009 ℰ	Ground anchor		
Spare parts Spare parts			
ZS1566zx0009	Service set.		

Files to download	
Photometric LDT files	Photometric IES files

Indexes		
Index	Color	RAL
1566BL	BLACK	9005
1566GR	GRAPHITE	7016
1566GA	HOT-DIP GALVANIZING	-





Manual

