



Type of luminaire

Type of luminaire	Post light fixture.
Photometric body	Light discovered
Characteristics of the luminaire	A luminaire with a modern design, in which a combination of a decorative crystal lampshade with a durable and stable structure of the luminaire.

General information

Materials	Hot-dip galvanized steel. Hot-dip galvanized and powder-coated steel. Lens - crystal glass, satin inside. The lampshade may take on an amber color over time.
Mounting method	Mounting of the luminaire: 2 holes \varnothing 6.8mm at a distance of 38mm
Terminal	Connection terminals: max 2x2.5mm ² Possibility of connecting the luminaire in loops of max. 2x2.5mm ² Round insulated cable with a maximum diameter of \varnothing 12.5mm
Type of light source	LED module AC integrated Replaceable (LED only) light source by a professional.
Light control	Phase-dimming (TRIAC) TRAILING EDGE (TE) - LEADING EDGE (LE)

Technical data

LED module	Yes
External control	Phase dimmer Lumens LED AC (User manual)
Light source wattage	4W
Luminaire wattage	4W
Lamp luminous flux	439lm
Luminaire luminous flux	330lm
Efficiency of the luminaire	82.5lm/W
Color temperature	3000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
LED photobiological threat	RG0 or RG1
Power Factor luminaire	PF>0,98
Ta Rated temperature	+25°C
Ambient operating temp. range	TA MAX=+65°C

This product contains light source of energy efficiency class **A** / **EPREL**

Inrush current	17mA / 60ms
BUG rating	B0-U3-G0

Accessories sold separately

204GA0009	Ground anchor
203ZX0009	Concreting anchor

Spare parts

ZS1566zx0009	Service set.
--------------	--------------

Files to download

Photometric LDT files	Photometric IES files
Manual	

Indexes

Index	Color	RAL
1566BL	BLACK	9005
1566GR	GRAPHITE	7016
1566GA	HOT-DIP GALVANIZING	-

Other colors according to the "Colors Template" pattern book - available on request, subject to agreement with Norlys' Sales Department.