

NORLYS KOSTER PRO 1822


AC 220-240V 50-60Hz | IP 65 | IK 10 | LED | DALI2

Koster pro
1822XX0010
22.09.2026 v.10.6
www.norlys.no









Type of luminaire

Type of luminaire	Wall, arm-mounted luminaire.
Photometric body	Lens from Ledil type VSM (IESNA type V)
Characteristics of the luminaire	Wall-mounted fixture on a straight arm with modern design. Can be installed on the corners of architectural objects. Wide, even light distribution.

General information

Materials	Powder painted aluminum cast. Lens - transparent polycarbonate with structure, UV stabilized.
Mounting method	Mounting the fixture: 3 holes ø7mm, spacing according to the included box. Other accessories must be ordered separately.
Terminal	Connection terminals: max 5x2.5mm², possibility of looping the fixture max 5x2.5mm². Round cable with a diameter of ø7...10.5mm.
Type of light source	LED module, electronic power supply Replaceable (LED only) light source by a professional. Replaceable control gear by a professional.
Light control	System light control: DALI outdoor full programm. The power supply is programmed for the maximum permitted current. Programming of other parameters after contact with the Norlys Sales Department.
Luminaire weight net / gross	2,86kg / 3,74kg
Box dimensions [cm]	43,5cm x 29cm x 24cm
Luminaire dimensions [cm]	44cm x 24,5cm x 24cm

Technical data

LED module	Philips Fortimo FastFlex LED 2x4 G5 3K (Datasheet)
Driver	Yes
Driver durability	100000h
External control	DALI2 / NightDim (XI FP NLD) (User manual)
Light source wattage	15,4W
Luminaire wattage	18,1W
Lamp luminous flux	2801lm
Luminaire luminous flux	1878lm
Efficiency of the luminaire	103,8lm/W
ULOR	0%
Color temperature	3000K
Colour consistency (McAdam ellipse)	SDCM5
Flicker of light (Pst LM)	≤0.1
Strobe effect (SVM)	≤0.1
Colour rendering index CRI	70
L90B10 [wg LM-80]	>100 000h
LED photobiological threat	RG0 or RG1
Power Factor luminaire	PF>0.98
THD factor	7%
Overvoltage	6 / 10kV
Ta Rated temperature	+25°C
Ambient operating temp. range	-20...+45°C

This product contains light source of energy efficiency class D / EPREL

Optionally, the fixture is also available:
- for LED color 2200K/2700K
- for a different luminous flux value
- for a different fixture color (according to the RAL color chart)

Terms of sale and other information can be arranged with the Norlys Sales Department.
Applique murale sur un bras droit au design moderne.
Possibilité de montage sur les angles des objets architecturaux.
Large distribution uniforme de la lumière.

Inrush current	15A / 295µsec
BUG rating	B1-U1-G1

Maximum number of luminaires of this type per MCB:

B 10A: 18, B 16A: 29, C 10A: 30, C 16A: 49

Norlys AS
P.B 1014 Hoff, 0218
Oslo
Hovfaret 4B, 0275
Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no

TÜVRheinland CERTIFIED — Management System ISO 9001:2015 IATF 16949:2016 — www.tuv.com ID 9108651873

PCC cert CERTIFICATE ISO 14001

RoHS 2011/65/UE

Before starting the installation, refer to the instructions attached to the fixture. Due to the dynamic development of lighting technology, additional information is provided upon customer request. Condensation that may occur in the fixtures is a natural phenomenon and does not affect the quality of the fixture.

KOSTER PRO 1822



Spare parts

4699100415	Service set LED
4699200201	Service set power supply
ZS1822zx0010	Service set.

Files to download

Photometric LDT files	Photometric IES files
Manual	

Indexes

Index	Color	RAL
1822AL	ALUMINUM	9006
1822GR	GRAPHITE	7016

Other colors according to the "Colors Template" / RAL pattern book - available on request, subject to agreement with Norlys' Sales Department.

Norlys AS
P.B 1014 Hoff, 0218
Oslo
Hovfaret 4B, 0275
Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no

TÜVRheinland CERTIFIED
Management System ISO 9001:2015 IATF 16949:2016
www.tuv.com ID 9108651873
PCC Cert CERTIFICATE ISO 14001
RoHS 2011/65/UE

Before starting the installation, refer to the instructions attached to the fixture. Due to the dynamic development of lighting technology, additional information is provided upon customer request. Condensation that may occur in the fixtures is a natural phenomenon and does not affect the quality of the fixture.