



Type of luminaire

Type of luminaire	Post light fixture.
Photometric body	Diffused light, covered from the top.
Characteristics of the luminaire	Modern design luminaire. For lighting gardens, private areas and public spaces

General information

Materials	Powder painted aluminum cast. Lens - transparent polycarbonate with structure, UV stabilized.
Mounting method	Fixing of the luminaire: 4 holes \varnothing 7mm, spacing 18x50mm.
Terminal	Connection terminals: max 3x2,5mm ² . Possibility to connect luminaire in max 3x1,5mm ² . Round insulated cable with a diameter of max \varnothing 6-10mm
Type of light source	LED module AC integrated Replaceable (LED only) light source by a professional.
Light control	Phase-dimming (TRIAC) TRAILING EDGE (TE) - LEADING EDGE (LE)
Luminaire weight net / gross	2kg / 2,39kg
Box dimensions [cm]	16cm x 11,2cm x 80cm

Technical data

LED module	Yes
External control	Phase dimmer Lumens LED AC (User manual)
Light source wattage	8W
Luminaire wattage	8W
Lamp luminous flux	890lm
Luminaire luminous flux	498lm
Efficiency of the luminaire	62,3lm/W
ULOR	2%
Color temperature	3000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
L70TM-21 [wg LM-80]	>55 000h
LED photobiological threat	RG0 or RG1
Power Factor luminaire	PF>0,99
THD factor	< 20%
Ta Rated temperature	+25°C
Ambient operating temp. range	Ta max=+65°C
Inrush current	2,9A/34 μ s
BUG rating	"B0-U1-G0"

Accessories sold separately

1907ZX0009	Concreting anchor
1908GA0009	Ground anchor
3090GA0009	Mounting adapter
1909GA0010	Adapter for concrete foundation
3081XX0009	Mounting adapter
1906ZX0009	Mounting adapter

Files to download

Photometric LDT files	Photometric IES files
Manual	

Indexes

Index	Color	RAL
1901AL	ALUMINUM	9006
1901GR	GRAPHITE	7016

Other colors according to the "Colors Template" pattern book - available on request, subject to agreement with Norlys' Sales Department.