

NORLYS KOSTER 1913


AC 220-240V 50-60Hz | IP 54 | IK 10 | LED

Koster 1913XX0011
04.11.2026 v.11.8
www.norlys.no









Type of luminaire

Type of luminaire	Pole luminaire.
Photometric body	Single-sided light: symmetrical, directed downward.
Characteristics of the luminaire	Classic design luminaire for mounting on a telescopic lighting pole with cap diameter Ø60mm.

General information

Materials	Powder painted aluminum cast. Lens - transparent polycarbonate with structure, UV stabilized.
Mounting method	Fixing of the luminaire: luminaire adjusted to lighting pole with cap diameter ø60mm.
Terminal	3.7m cable (H05VV-F 3G1 type), for connection inside the lighting pole (in the appropriately selected electrical installation box).
Type of light source	LED module AC integrated Replaceable (LED only) light source by a professional.
Light control	Non-dimmable fixture
Luminaire weight net / gross	3,25kg / 3,92kg
Box dimensions [cm]	46cm x 29cm x 25cm
Luminaire dimensions [cm]	45cm x 24,5cm x 24,5cm
Side area of luminaire	0,045m^2

Technical data

LED module	Philips Fortimo DLM ES 2000/8xx G2 3K (Datasheet)
Light source wattage	17,5W
Luminaire wattage	17,5W
Lamp luminous flux	1950lm
Luminaire luminous flux	1568lm
Efficiency of the luminaire	89,6lm/W
ULOR	0%
Color temperature	3000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
L70TM-21 [wg LM-80]	>50 000h
Power Factor luminaire	PF > 0,9
Ta Rated temperature	+25°C
Ambient operating temp. range	-20...+45°C
This product contains light source of energy efficiency class E / EPREL	
Inrush current	3,01A/32,66µs
BUG rating	B1-U1-G0

Accessories sold separately

7660XX0009	Reduction

Spare parts

06710000	Lampshade - service kit
46999751	LED module.

Files to download

Photometric LDT files	Photometric IES files
Manual	BIM Revit
BIM ArchiCAD	

Indexes

Index	Color	RAL
1913AL	ALUMINUM	9006
1913GR	GRAPHITE	7016

Other colors according to the "Colors Template" / RAL pattern book - available on request, subject to agreement with Norlys' Sales Department.

Norlys AS
P.B 1014 Hoff, 0218
Oslo
Hovfaret 4B, 0275
Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no

TÜVRheinland CERTIFIED — Management System ISO 9001:2015 IATF 16949:2016 — www.tuv.com ID 9108651873

PCC Cert CERTIFICATE ISO 14001

RoHS 2011/65/UE

Please read the manual before installing. Due to the dynamic development of lighting technology, additional information is available upon request. LED module must be replaced by a qualified person in accordance with applicable regulations. Condensation, which can occur in luminaires, is a natural phenomenon and does not impair the quality of the luminaire.