

NORLYS VOSS 1952


AC 220-240V 50-60Hz | IP 54 | IK 06 | LED | No Dim

Voss 1952XX0F10
02.11.2026 v.10.14
www.norlys.no









Type of luminaire

Type of luminaire	Wall light,
Photometric body	Double-sided light with 62° beam angle facing up and down.
Characteristics of the luminaire	A luminaire with a wide range of applications, for lighting: walls, facades surfaces, and other architectural concepts

General information

Materials	Powder painted aluminum cast. Lampshade - safety glass, transparent. Silicone gasket. EPDM cable gland.
Mounting method	Mounting of the luminaire: 2 holes ø7mm, spacing 100x80mm According to the attached assembly instructions
Terminal	Connection terminals: max 3x2.5mm² Possibility of connecting the luminaire in loops of max. 3x1.5mm² Round insulated cable with a diameter of ø7...10.5mm
Type of light source	LED module, electronic power supply Replaceable (LED only) light source by a professional. Replaceable control gear by a professional.
Light control	Non-dimmable fixture
Luminaire weight net / gross	4,57kg / 5,03kg
Box dimensions [cm]	22,5cm x 19,5cm x 32cm
Luminaire dimensions [cm]	18cm x 16cm x 27cm

Technical data

4 LED modules.	Cree DK180501 V8 JB2835 3V 3K (Datasheet)
Driver	Yes
Driver durability	50000h
Light source wattage	16,6W
Luminaire wattage	18,9W
Lamp luminous flux	2888lm
Luminaire luminous flux	1218lm
Efficiency of the luminaire	64,4lm/W
ULOR	50%
Color temperature	3000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
L80TM-21 [wg LM-80]	>102 000h
L90 TM-21 [wg LM-80]	>52 600h
Power Factor luminaire	PF 0,90
THD factor	20%
Ta Rated temperature	+25°C
Ambient operating temp. range	-20...+45°C
This product contains light sources of energy efficiency class C / EPREL	
Inrush current	4,4A / 66µs
BUG rating	B1-U4-G0

Spare parts

ZS1952zx0F10	LED module.

Files to download

Photometric LDT files	Photometric IES files
Manual	BIM Revit
BIM ArchiCAD	

Indexes

Index	Color	RAL
1952AL	ALUMINUM	9006
1952GR	GRAPHITE	7016

Other colors according to the "Colors Template" / RAL pattern book - available on request, subject to agreement with Norlys' Sales Department.

Norlys AS
P.B 1014 Hoff, 0218
Oslo
Hovfaret 4B, 0275
Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no

TÜVRheinland CERTIFIED — Management System ISO 9001:2015 IATF 16949:2016 — www.tuv.com ID 9108651873

PCC Cert CERTIFICATE ISO 14001

RoHS 2011/65/UE

Before the assembly, read the instructions attached to the luminaire. Installation and service work is carried out by a person with appropriate authorizations and qualifications, in accordance with applicable regulations. Due to the dynamic development of lighting technology, we provide additional information on request.
Condensation that may occur in the luminaires is a natural phenomenon and does not affect the quality of the luminaire