

























Type of luminaire		
Type of lumianire	Ceiling fixture.	
Photometric body	Single-sided light with 24° beam angle facing down	
Characteristics of the luminaire	A luminaire with a wide range of applications mounted on horizontal surfaces, including lighting: walls, facade surfaces and other architectuconcepts	

Generalinformation		
Materials	Powder painted aluminum cast. Lampshade - safety glass, transparent.	
Mounting method	Mounting of the luminaire: 2 holes, spacing 80mm According to the attached instructions	
Terminal	Connection terminals: max 3x2,5mm² Possibility of connecting the luminaire in loops of max 1,5mm² Round insulated cable with a diameter of ø710,5mm	
Type of light source	LED module, electronic power supply Replaceable (LED only) light source by a professional. Replaceable control gear by a professional.	
Light control	Phase-dimming (TRIAC) TRAILING EDGE (TE) - LEADING EDGE (LE)	
Net/gross weight of luminaire	1,47kg/1,62kg	
Box dimensions [cm]	21cmx13cmx13cm	
Luminaire dimensions [cm]	18cmx12cmx12cm	

Technical data		
Driver durability	50000h	
External control	Dim. TRIAC (KGP) (User manual)	
Luminaire wattage	7,8W	
Luminaire luminous flux	765lm	
Efficiency of the luminaire	98,1lm/W	
Color temperature	3000K	
Colour consistency (McAdam ellipse)	SDCM3	
Flicker of light (Pst LM)	≤0.4	
Strobe effect (SVM)	≤0.1	
Colour rendering index CRI	80	
Rated life time L70/B50 at 25°C	50 000h	
Power Factor luminaire	PF 0,90	
THD factor	15%	
Ta Rated temperature	+25°C	
Ambient temperature	Ta max=+65°C	

This product contains light source of energy efficiency class ${}^{\textcircled{1}}$ / \mathscr{E} EPREL

Optionally, the luminaire is also available: - For the LED color 2700K [1/1]

For a different color of the fitting (according to the RAL color palette)
Terms of sale and other information, after contact with the Sales Department of Norlys

Inrush current	8A/10µs	
BUG rating	B1-U1-G0	

Spare parts

ZS2121zx0009 Service set.

Files to download

Photometric LDT files Photometric IES files

Manual

Indexes		
Index	Color	RAL
2121AL	ALUMINUM	9006
2121BL	BLACK	9005
2121GR	GRAPHITE	7016
2121WH	WHITE	9003





