

NORLYS FRIGGA 2154


IP 65 | IK 06 | LED | DALI2

Frigga 2154XX0009
16.09.2026 v.09.17
www.norlys.no









Type of luminaire

Type of luminaire	Bollard.
Photometric body	Light discovered
Characteristics of the luminaire	A fixture with modern design, combining a decorative crystal shade with a durable and stable housing.

General information

Materials	Extruded aluminum profile, powder coated. Lens - crystal glass, satin inside. The lampshade may take on an amber color over time. EPDM cable gland.
Mounting method	Mounting the fixture: 3 holes Ø9mm, on a Ø65mm diameter at 120° intervals. Other accessories must be purchased separately.
Terminal	Connection terminals: max 5x2.5mm², possibility of looping the fixture max 5x2.5mm². Cable in a round jacket with a maximum diameter of ø12.5mm.
Type of light source	LED module, DALI electronic power supply Replaceable light source by a professional. Replaceable control gear by a professional.
Light control	Light control - DALI system
Luminaire weight net / gross	8,3kg / 9,5kg
Box dimensions [cm]	120cm x 17cm x 17cm
Luminaire dimensions [cm]	14cm x 14cm x 85cm

Technical data

LED module	Philips Fortimo SLM C 1203 L09 1619 G7 4K (Datasheet)
Driver	Yes
Driver durability	100000h
Light source wattage	4,6W
Luminaire wattage	4,7W
Luminaire luminous flux	335lm
Efficiency of the luminaire	71,3lm/W
ULOR	85%
Color temperature	4000K
Colour consistency (McAdam ellipse)	SDCM3
Flicker of light (Pst LM)	≤1
Strobe effect (SVM)	≤0.4
Colour rendering index CRI	80
L70TM-21 [wg LM-80]	>50 000h
LED photobiological threat	RG0 or RG1
Power Factor luminaire	PF=0.9
Ta Rated temperature	TA +35°C
Ambient operating temp. range	-20...+45°C
This product contains light source of energy efficiency class D / EPREL	
Inrush current	6.7A/2.4us

Maximum number of luminaires of this type per MCB:

B 10A: 46, B 16A: 74, C 10A: 74, C 16A: 119

Accessories sold separately

3080GA0009	Mounting adapter
205ZX0010	Concreting anchor
206GA0010	Ground anchor
206GA0S10	Adapter for concrete foundation

Spare parts

0921530010	Lampshade - service kit
ZN2154xx0009	Service set.

Norlys AS
P.B 1014 Hoff, 0218
Oslo
Hovfaret 4B, 0275
Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no

Management System ISO 9001:2015 IATF 16949:2016 TÜVRheinland CERTIFIED www.tuv.com ID 9108651873

PCC Cert CERTIFICATE ISO 14001

RoHS 2011/65/UE

Before starting the assembly, read the instructions attached to the fixture. Assembly and service work is carried out by a person with appropriate authorizations and qualifications, in accordance with applicable regulations. Condensation, which may occur in fixtures, is a natural phenomenon and does not affect the deterioration of the quality of the fixture.

Files to download

Photometric LDT files	Photometric IES files
Manual	

Indexes

Index	Color	RAL
2154AL	ALUMINUM	9006
2154BL	BLACK	9005
2154CG	CEMENT GREY	7033
2154CB	COPPER BROWN	8004
2154CS	CORTEN STEEL	approx. 8011
2154GR	GRAPHITE	7016
2154GB	GREY BEIGE	7006
2154WH	WHITE	9003

Other colors according to the "Colors Template" pattern book - available on request, subject to agreement with Norlys' Sales Department.

Norlys AS
P.B 1014 Hoff, 0218
Oslo
Hovfaret 4B, 0275
Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no

Management System ISO 9001:2015 IATF 16949:2016
www.tuv.com ID 9108651873

CERTIFICATE ISO 14001

RoHS 2011/65/UE

Before starting the assembly, read the instructions attached to the fixture. Assembly and service work is carried out by a person with appropriate authorizations and qualifications, in accordance with applicable regulations. Condensation, which may occur in fixtures, is a natural phenomenon and does not affect the deterioration of the quality of the fixture.