


NORLYS HELLVIK 2406


IP 65 | IK 08 | LED | DALI2

Hellvik 2406XX0009
29.10.2026 v.09.23
www.norlys.no









Type of luminaire

Type of luminaire	Post light fixture.
Photometric body	Diffused light, covered from the top.
Characteristics of the luminaire	A fixture with contemporary design. For lighting gardens, private areas, and other architectural applications. Suitable for emergency installations on direct current: DC 176 ÷ 276V

General information

Materials	Powder painted aluminum cast. Lens - transparent polycarbonate with structure, UV stabilized. Silicone gasket.
Mounting method	The product includes fastening elements for installation: 4x threaded rod type L M6x150x75 ZINC-COATED; 4x nut M6 DIN 934 A-2; 4x flat washer FI 6 DIN 125 A2. Installation should be carried out according to the attached instructions. Other accessories should be purchased separately.
Terminal	Connection terminals: max 5x2.5mm², option to loop the fitting: max 5x2.5mm². Cable in a round sheath with a diameter of max ø12.5mm.
Type of light source	LED module, electronic power supply Replaceable (LED only) light source by a professional. Replaceable control gear by a professional.
Light control	Light control - DALI system
Luminaire weight net / gross	7,94kg / 8,66kg
Box dimensions [cm]	46cm x 15cm x 57cm
Luminaire dimensions [cm]	42cm x 11cm x 55cm

Technical data

LED module	Philips Fortimo FastFlex LED 2x6 DP G5 3K (Datasheet)
Driver	Yes
Driver durability	100000h
Light source wattage	9,9W
Luminaire wattage	11,9W
Lamp luminous flux	1691lm
Luminaire luminous flux	1537lm
Efficiency of the luminaire	129,2lm/W
ULOR	3%
Color temperature	3000K
Colour consistency (McAdam ellipse)	SDCM5
Flicker of light (Pst LM)	≤1
Strobe effect (SVM)	≤0.4
Colour rendering index CRI	70
L90B10 [wg LM-80]	>100 000h
Power Factor luminaire	PF 0,95
THD factor	< 10%
Ta Rated temperature	+25°C
Ambient operating temp. range	-20...+45°C

This product contains light source of energy efficiency class D / EPREL

Optionally, the luminaire is also available:
- for a different luminous flux value.
- for a different luminaire color (according to the RAL color palette).
Sales conditions and other information can be provided upon agreement with the Norlys Sales Department.
Luminaire au design contemporain.
Pour l'éclairage des jardins, des terrains privés et d'autres applications architecturales.
Convient aux installations d'urgence sur tension continue : DC 176 ÷ 276V.

Inrush current	20A / 200µs
BUG rating	B1-U2-G1

Accessories sold separately

209GA0009	Ground anchor
209GA0S09	Adapter for concrete foundation

Norlys AS
P.B 1014 Hoff, 0218
Oslo
Hovfaret 4B, 0275
Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no

TÜVRheinland CERTIFIED — Management System ISO 9001:2015 IATF 16949:2016 — www.tuv.com ID 9108651873

PCC Cert CERTIFICATE ISO 14001

RoHS 2011/65/UE

Before starting the installation, please read the instructions attached to the fixture. Installation and maintenance work should be carried out by a person with the appropriate authorizations and qualifications, in accordance with applicable regulations. Due to the dynamic development of lighting technology, additional information is provided upon customer request. Condensation that may occur in the fixtures is a natural phenomenon and does not affect the quality of the fixture.

Spare parts

4699100402	LED module.
4699210400	Power supply.
ZS2406zx0009	Repair kit.

Files to download

Photometric LDT files	Photometric IES files
Manual	

Indexes

Index	Color	RAL
2406AL	ALUMINUM	9006
2406BL	BLACK	9005
2406CG	CEMENT GREY	7033
2406CB	COPPER BROWN	8004
2406CS	CORTEN STEEL	approx. 8011
2406GM	GRAIN MINERAL	-
2406GR	GRAPHITE	7016
2406GB	GREY BEIGE	7006
2406WH	WHITE	9003

Other colors according to the "Colors Template" / RAL pattern book - available on request, subject to agreement with Norlys' Sales Department.

Norlys AS
P.B 1014 Hoff, 0218
Oslo
Hovfaret 4B, 0275
Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no

Management System ISO 9001:2015 IATF 16949:2016
www.tuv.com ID 9108651873

CERTIFICATE ISO 14001

RoHS 2011/65/UE

Before starting the installation, please read the instructions attached to the fixture. Installation and maintenance work should be carried out by a person with the appropriate authorizations and qualifications, in accordance with applicable regulations. Due to the dynamic development of lighting technology, additional information is provided upon customer request. Condensation that may occur in the fixtures is a natural phenomenon and does not affect the quality of the fixture.