


NORLYS HELLVIK MINI 2434


IP 65 | IK 08 | AC 220-240V 50-60Hz | LED | DIM

Hellvik Mini
2434XX0009
16.11.2026 v.09.17
www.norlys.no









Type of luminaire

Type of luminaire	Post light fixture.
Photometric body	Lens VSM CS15763 STRADA 2x2MX-8-VSM
Characteristics of the luminaire	A fixture with contemporary design. For lighting gardens, private areas, and other architectural applications.

General information

Materials	Extruded aluminum profile, powder coated. The outer hermetic lens - transparent PMMA plastic Silicone gasket.
Mounting method	According to the attached assembly instructions. Additional accessories need to be purchased separately.
Terminal	Connection terminals: max 3x2.5mm². Option to connect the fixture in a loop max 3x1.5mm². Cable in a round sheath with a diameter max ø12.5mm.
Type of light source	LED module, electronic power supply Replaceable (LED only) light source by a professional. Replaceable control gear by a professional.
Light control	Trailing edge (TE) dimming
Luminaire dimensions [cm]	26cm x 11cm x 55cm

Technical data

LED module	Cree DK200402 V1 XTE-HE 3K (Datasheet)
Driver	Yes
Driver durability	50000h
Light source wattage	5,8W
Luminaire wattage	7,2W
Lamp luminous flux	828lm
Luminaire luminous flux	469lm
Luminous intensity of the luminaire	347cd
Efficiency of the luminaire	65,1lm/W
ULOR	2%
Color temperature	3000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
L90 TM-21 [wg LM-80]	>109 000h
LED photobiological threat	RG0 or RG1
Power Factor luminaire	PF>0,89
Ta Rated temperature	+25°C
Ambient operating temp. range	-20...+45°C

This product contains light source of energy efficiency class G / EPREL

Optionally, the fixture is also available:
- for a different luminous flux value
- in a version with a surge protection device (SPD)
- for a different fixture color (according to RAL color palette)
- for a different fixture height

Sales conditions and other information are subject to agreement with the Sales Department of the company Norlys.

Accessories sold separately

199GA0S09	Adapter for concrete foundation
199GA0009	Ground anchor

Files to download

Photometric LDT files	Photometric IES files
Manual	

Norlys AS
P.B 1014 Hoff, 0218
Oslo
Hovfaret 4B, 0275
Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no

TÜVRheinland CERTIFIED — Management System ISO 9001:2015 IATF 16949:2016 — www.tuv.com ID 9108651873

PCC Cert CERTIFICATE ISO 14001

RoHS 2011/65/UE

Before starting the installation, please refer to the instructions included with the fixture. Installation and maintenance work should be carried out by a person with appropriate authorizations and qualifications, in accordance with applicable regulations. Due to the dynamic development of lighting technology, additional information is provided at the customer's request. Condensation that may occur in fixtures is a natural phenomenon and does not adversely affect the quality of the fixture.

HELLVIK MINI 2434



Indexes

Index	Color	RAL
2434AL	ALUMINUM	9006
2434BL	BLACK	9005
2434CG	CEMENT GREY	7033
2434CB	COPPER BROWN	8004
2434CS	CORTEN STEEL	approx. 8011
2434GM	GRAIN MINERAL	-
2434GR	GRAPHITE	7016
2434GB	GREY BEIGE	7006
2434WH	WHITE	9003

Other colors according to the "Colors Template" / RAL pattern book - available on request, subject to agreement with Norlys' Sales Department.

Norlys AS
P.B 1014 Hoff, 0218
Oslo
Hovfaret 4B, 0275
Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no

TÜVRheinland CERTIFIED
Management System ISO 9001:2015 IATF 16949:2016
www.tuv.com ID 9108651873

PCC Cert CERTIFICATE ISO 14001

RoHS 2011/65/UE

Before starting the installation, please refer to the instructions included with the fixture. Installation and maintenance work should be carried out by a person with appropriate authorizations and qualifications, in accordance with applicable regulations. Due to the dynamic development of lighting technology, additional information is provided at the customer's request. Condensation that may occur in fixtures is a natural phenomenon and does not adversely affect the quality of the fixture.