NORLYS BOLOGNA 3025

AC 220-240V 50-60Hz | IP 54 | E27

Bologna
3025XX0010
16.09.2026 v.10.3
www.norlys.no



Type of luminaire

Photometric body	Diffused light.
Characteristics of the luminaire	Classic design luminaire, dedicated to be mounted on a telescopic lighting pole.

General information

Materials	Powder painted aluminum cast. Lens - transparent plastic PMMA. Silicone gasket.
Mounting method	Fixing of the luminaire: dedicated to be mounted on a telescopic lighting pole.
Terminal	Connection terminals: max 4x2.5mm², possibility of connecting the fixture in a loop max 4x2.5mm². Cable in a round sleeve with a diameter of ø7...12.5mm.
Type of light source	Lamp E27 A55...A60 Replaceable light source by an end-user.
Box dimensions [cm]	49cm x 37cm x 32,5cm

Technical data

Lamp E27	LED A55..60
Light source wattage	LED max 9W
Ta Rated temperature	+25°C
Ambient operating temp. range	-20...+45°C

Possibility to order the fixture with a Philips Master LEDbulb E27 806lm/8.5W/2700K (dimmable).

Spare parts

06360008	Lampshade - service kit

Files to download

Manual

Indexes

Index	Color	RAL
3025BL	BLACK	9005
3025WH	WHITE	9003

Other colors according to the "Colors Template" pattern book - available on request, subject to agreement with Norlys' Sales Department.

Norlys AS
P.B 1014 Hoff, 0218
Oslo
Hovfaret 4B, 0275
Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no

TÜVRheinland CERTIFIED
Management System ISO 9001:2015 IATF 16949:2016
www.tuv.com ID 9108651873

PCC Cert CERTIFICATE ISO 14001

RoHS 2011/65/UE

Please read the manual before installing. Due to the dynamic development of lighting technology, additional information is available upon request. LED module must be replaced by a qualified person in accordance with applicable regulations. Condensation, which can occur in luminaires, is a natural phenomenon and does not impair the quality of the luminaire.