

NORLYS LONDON 4144


AC 220-240V 50-60Hz | IP 54 | IK 07 | LED

London 4144XX0009
16.09.2026 v.09.11
www.norlys.no









Type of luminaire

Type of luminaire	Platform-Light design element
Photometric body	Light discovered
Characteristics of the luminaire	A pillar-type luminaire with a classic design. Used for lighting gardens, terraces, and other architectural concepts.

General information

Materials	Powder painted aluminum cast.
Mounting method	Fixture mounting: 2 holes ø5.5mm, spacing 90mm. For mounting on substrate, wall, platform, and other structures.
Terminal	Connection terminals: max 2x2.5mm², possibility of looping the fitting max 2x2.5mm². Cable in a round sheath with a diameter of ø7...10.5mm.
Type of light source	LED module AC integrated Replaceable (LED only) light source by a professional.
Luminaire weight net / gross	3,9kg / 5,3kg
Box dimensions [cm]	32,5cm x 43cm x 65cm
Luminaire dimensions [cm]	30cm x 30cm x 64cm

Technical data

LED module	Philips Fortimo DLM ES 1100/8xx G2 3K (Datasheet)
Light source wattage	9,5W
Luminaire wattage	9,3W
Lamp luminous flux	1100lm
Luminaire luminous flux	756lm
Efficiency of the luminaire	81,3lm/W
ULOR	0%
Color temperature	3000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
L70TM-21 [wg LM-80]	>50 000h
Power Factor luminaire	PF>0,9
Ta Rated temperature	+25°C
Ambient operating temp. range	-20...+45°C
This product contains light source of energy efficiency class E / EPREL	
Inrush current	3,01A/32,66µs

Files to download

Photometric LDT files	Photometric IES files
Manual	

Indexes

Index	Color	RAL
4144BL	BLACK	9005
4144WH	WHITE	9003

Other colors according to the "Colors Template" pattern book - available on request, subject to agreement with Norlys' Sales Department.

Norlys AS
P.B 1014 Hoff, 0218
Oslo
Hovfaret 4B, 0275
Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no

TÜVRheinland CERTIFIED — Management System ISO 9001:2015 IATF 16949:2016 — www.tuv.com ID 9108651873

PCC Cert CERTIFICATE ISO 14001

RoHS 2011/65/UE

Before starting installation, it is necessary to read the instructions included with the fixture.
Due to the dynamic development of lighting technology, we provide additional information at the customer's request.
Condensation that may occur in the fixtures is a natural phenomenon and does not affect the quality of the fixture.