

NORLYS ASKER HEAD 4304


AC 220-240V 50-60Hz | IP 65 | IK 10 | LED | DALI2

ASKER HEAD
4304XX0009
16.09.2026 v.09.7
www.norlys.no









Type of luminaire

Type of luminaire	Pole luminaire.
Photometric body	Ledil lens type SCL (IESNA type II / III)
Characteristics of the luminaire	Top-mounted luminaire, designed for installation on a lighting pole with a mounting socket Ø50mm; Ø60mm; Ø76mm Wide and even light distribution. Luminaire also adapted for DC voltage: 168 ÷ 275 V

General information

Materials	Extruded aluminum profile, powder coated. Hermetic external lens - transparent PC plastic.
Mounting method	Mounting of the fixture: the fixture is adapted to a pole Ø 50, Ø 60, Ø 76, according to the installation instructions. Other accessories must be ordered separately
Terminal	Luminaire equipped with a 6m long H05BQ-F 5G1 type cable. For connection in a properly selected electrical installation box.
Type of light source	Optical kit with IP67 (LED module and lens); electronic power supply Replaceable (LED only) light source by a professional. Replaceable control gear by a professional.
Light control	System light control: DALI outdoor full programm. The power supply is programmed for the maximum permitted current. Programming of other parameters after contact with the Norlys Sales Department.
Luminaire weight net / gross	2,5kg / 2,78kg
Box dimensions [cm]	50,5cm x 12,5cm x 8,5cm
Luminaire dimensions [cm]	47cm x 11cm x 7cm

Technical data

LED module	Philips Fortimo FastFlex LED 2x6 DP G5 3K (Datasheet)
Driver	Yes
Driver durability	100000h
External control	DALI2 / NightDim (XI FP NLD) (User manual)
Light source wattage	16,8W
Luminaire wattage	19,5W
Lamp luminous flux	2904lm
Luminaire luminous flux	2624lm
Efficiency of the luminaire	134,6lm/W
ULOR	0,8%
Color temperature	3000K
Colour consistency (McAdam ellipse)	SDCM5
Colour rendering index CRI	70
L90B10 [wg LM-80]	>100 000h
Power Factor luminaire	PF 0,98
Ta Rated temperature	+25°C
Ambient operating temp. range	-20...+45°C
This product contains light source of energy efficiency class D / EPREL	
BUG rating	B1-U2-G1

Accessories sold separately

7711XX0009	Mounting adapter
7713XX0009	Mounting adapter
7712XX0009	Mounting adapter

Files to download

Photometric LDT files	Photometric IES files
Manual	

Norlys AS
P.B 1014 Hoff, 0218
Oslo
Hovfaret 4B, 0275
Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no

TÜVRheinland CERTIFIED
Management System ISO 9001:2015 IATF 16949:2016
www.tuv.com ID 9108651873
PCC Cert CERTIFICATE ISO 14001
RoHS 2011/65/UE

ASKER HEAD 4304

Indexes

Index	Color	RAL
4304AL	ALUMINUM	9006
4304BL	BLACK	9005
4304GR	GRAPHITE	7016

Other colors according to the "Colors Template" pattern book - available on request, subject to agreement with Norlys' Sales Department.

Norlys AS
P.B 1014 Hoff, 0218
Oslo
Hovfaret 4B, 0275
Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no