

NORLYS ASKER HEAD 4305


AC 220-240V 50-60Hz | IP 65 | IK 10 | LED | DALI2

ASKER HEAD
4305XX0009
16.09.2026 v.09.6
www.norlys.no









Type of luminaire

Type of luminaire	Pole luminaire.
Photometric body	Ledil lens type SCL (IESNA type II / III)
Characteristics of the luminaire	Mounted luminaire, designed for installation on a lighting pole with a mounting shank Ø50mm; Ø60mm; Ø76mm. Wide, even light distribution. Luminaire also adapted for direct current voltage: DC 168 ÷ 275 V.

General information

Materials	Extruded aluminum profile, powder coated. Hermetic external lens - transparent PC plastic.
Mounting method	Fixture mounting: the fixture is suitable for poles Ø 50, Ø 60, Ø 76, according to the installation instructions. Other accessories must be ordered separately.
Terminal	The fixture is equipped with an H05BQ-F 5G1 cable with a length of 6m. For connection in a suitably selected electrical installation box.
Type of light source	Optical kit with IP67 (LED module and lens); electronic power supply Replaceable (LED only) light source by a professional. Replaceable control gear by a professional.
Light control	System light control: DALI outdoor full programm. The power supply is programmed for the maximum permitted current. Programming of other parameters after contact with the Norlys Sales Department.
Luminaire weight net / gross	2,5kg / 2,78kg
Box dimensions [cm]	50,5cm x 12,5cm x 8,5cm
Luminaire dimensions [cm]	47cm x 11cm x 7cm

Technical data

LED module	Philips Fortimo FastFlex LED 2x6 DP G5 4K (Datasheet)
Driver	Yes
Driver durability	100000h
External control	DALI2 / NightDim (XI FP NLD) (User manual)
Light source wattage	16,8W
Luminaire wattage	19,5W
Lamp luminous flux	3036lm
Luminaire luminous flux	2742lm
Efficiency of the luminaire	140,6lm/W
ULOR	0,8%
Color temperature	4000K
Colour consistency (McAdam ellipse)	SDCM4
Colour rendering index CRI	70
L90B10 [wg LM-80]	>100 000h
Power Factor luminaire	PF 0,98
Ta Rated temperature	+25°C
Ambient operating temp. range	-20...+45°C
This product contains light source of energy efficiency class D / EPREL	
BUG rating	B1-U2-G1

Accessories sold separately

7711XX0009	Mounting adapter
7713XX0009	Mounting adapter
7712XX0009	Mounting adapter

Files to download

Photometric LDT files	Photometric IES files
Manual	

Norlys AS
P.B 1014 Hoff, 0218
Oslo
Hovfaret 4B, 0275
Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no

TÜVRheinland CERTIFIED Management System ISO 9001:2015 IATF 16949:2016 www.tuv.com ID 9108651873

PCC Cert CERTIFICATE ISO 14001

RoHS 2011/65/UE

ASKER HEAD 4305

Indexes

Index	Color	RAL
4305AL	ALUMINUM	9006
4305BL	BLACK	9005
4305GR	GRAPHITE	7016

Other colors according to the "Colors Template" pattern book - available on request, subject to agreement with Norlys' Sales Department.

Norlys AS
P.B 1014 Hoff, 0218
Oslo
Hovfaret 4B, 0275
Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no