

NORLYS ASKER HEAD 4353


AC 220-240V 50-60Hz | IP 65 | IK 10 | LED | DALI2

ASKER HEAD
4353XX0309
16.09.2026 v.09.6
www.norlys.no









Type of luminaire

Type of luminaire	Pole luminaire.
Photometric body	Ledil lens type SCL (IESNA type II / III)
Characteristics of the luminaire	A mounted luminaire designed for installation on a lighting pole with a mounting base Ø60mm. Wide even light distribution. Luminaire also compatible with DC voltage: DC 168 ÷ 275 V

General information

Materials	Extruded aluminum profile, powder coated. Hermetic external lens - transparent PC plastic.
Mounting method	Luminaire mounting: luminaire adapted to a Ø 60 pole in accordance with the installation instructions. Set composition: art.7711 - bracket Ø60 art.4311 - luminaire
Terminal	The fixture is equipped with a H05BQ-F 5G1 type cable, 6m in length. To be connected in a properly selected electrical installation box.
Type of light source	Optical kit with IP67 (LED module and lens); electronic power supply Replaceable (LED only) light source by a professional. Replaceable control gear by a professional.
Light control	System light control: DALI outdoor full programm. The power supply is programmed for the maximum permitted current. Programming of other parameters after contact with the Norlys Sales Department.
Luminaire weight net / gross	2,5kg / 2,7kg
Box dimensions [cm]	50,5cm x 12,5cm x 8,5cm
Luminaire dimensions [cm]	47cm x 11cm x 7cm

Technical data

LED module	Philips Fortimo FastFlex LED 2x6 DP G5 4K (Datasheet)
Driver	Yes
Driver durability	100000h
External control	DALI2 / NightDim (XI FP NLD) (User manual)
Light source wattage	35,6W
Luminaire wattage	39,8W
Lamp luminous flux	6342lm
Luminaire luminous flux	5723lm
Efficiency of the luminaire	143,8lm/W
ULOR	0,8%
Color temperature	4000K
Colour consistency (McAdam ellipse)	SDCM4
Colour rendering index CRI	70
L90B10 [wg LM-80]	>100 000h
Power Factor luminaire	PF 0,97
Ta Rated temperature	+25°C
Ambient operating temp. range	-20...+45°C
This product contains light source of energy efficiency class D / EPREL	
BUG rating	B2-U2-G2

Accessories sold separately

7711XX0009	Mounting adapter
7712XX0009	Mounting adapter

Files to download

Photometric LDT files	Photometric IES files
Manual	

Norlys AS
P.B 1014 Hoff, 0218
Oslo
Hovfaret 4B, 0275
Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no

TÜVRheinland CERTIFIED — Management System ISO 9001:2015 IATF 16949:2016 — www.tuv.com ID 9108651873

PCC Cert CERTIFICATE ISO 14001

RoHS 2011/65/UE

ASKER HEAD 4353



Indexes

Index	Color	RAL
4353AL	ALUMINUM	9006
4353BL	BLACK	9005
4353GR	GRAPHITE	7016

Other colors according to the "Colors Template" pattern book - available on request, subject to agreement with Norlys' Sales Department.

Norlys AS
P.B 1014 Hoff, 0218
Oslo
Hovfaret 4B, 0275
Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no

Management System
ISO 9001:2015
IATF 16949:2016
TÜVRheinland CERTIFIED
www.tuv.com
ID 9108651873
PCC Cert
CERTIFICATE
ISO 14001
RoHS
2011/65/UE