
NORLYS LONDON 493

AC 220-240V 50-60Hz | IP 54 | IK 07 | E27





Type of luminaire

Type of luminaire	Wall light,
Photometric body	Light discovered
Characteristics of the luminaire	Classic type, wall-mounted luminaire for general use. Possibility to install on corners of architectural objects.

General information

Materials	Powder painted aluminum cast. Lens - clear polycarbonate, UV stabilized. EPDM cable gland.
Mounting method	Fixing of the luminaire: 4 holes ø5mm, spacing 25x140mm.
Terminal	Connection terminals: max 2x2,5mm². A round wire in the isolation with a diameter of ø7...10,5mm.
Type of light source	Lamp E27 A55...A60 Replaceable light source by an end-user.
Luminaire weight net / gross	3,57kg / 4,94kg
Box dimensions [cm]	53,2cm x 43,2cm x 31cm
Luminaire dimensions [cm]	30,5cm x 46cm x 56cm

Technical data

Lamp E27	LED A55..67
Light source wattage	LED max 11W
Luminaire wattage	LED max 11W
Ta Rated temperature	+25°C
Ambient operating temp. range	-20...+45°C

Accessories sold separately

30101XX0011	Telescopic pole
3010XX0011	Telescopic pole
152XX0009	Corner bracket

Spare parts

0904900051	Lampshade - service kit

Files to download

Manual

Indexes

Index	Color	RAL
493BL	BLACK	9005
493WH	WHITE	9003

Other colors according to the "Colors Template" pattern book - available on request, subject to agreement with Norlys' Sales Department.

Norlys AS
P.B 1014 Hoff, 0218
Oslo
Hovfaret 4B, 0275
Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no

TÜVRheinland CERTIFIED
Management System ISO 9001:2015 IATF 16949:2016
www.tuv.com ID 9108651873
PCC Cert CERTIFICATE ISO 14001
RoHS 2011/65/UE

Please read the manual before installing. Due to the dynamic development of lighting technology, additional information is available upon request. LED module must be replaced by a qualified person in accordance with applicable regulations. Condensation, which can occur in luminaires, is a natural phenomenon and does not impair the quality of the luminaire.