

NORLYS KOSTER 5004


AC 220-240V 50-60Hz | IP 54 | IK 10 | LED | No Dim

Koster 5004XX0012
02.11.2026 v.12.7
www.norlys.no









Type of luminaire

Type of luminaire	Wall, arm-mounted luminaire.
Photometric body	Single-sided light: symmetrical, directed downward.
Characteristics of the luminaire	Classic type wall-mounted luminaire. Possibility to install on corners of architectural objects.

General information

Materials	Powder painted aluminum cast. Lens - transparent polycarbonate with structure, UV stabilized.
Mounting method	Fixing of the luminaire: 3 holes ø7mm, spacing according to the enclosed mounting box.
Terminal	Connection terminal: max. 3x2.5mm² cable, possibility to connect luminaire in loop max. 3x1,5mm². A round wire in the isolation with a diameter of ø7...10,5mm.
Type of light source	LED module AC integrated Replaceable (LED only) light source by a professional.
Light control	Non-dimmable fixture
Luminaire weight net / gross	2,87kg / 3,72kg
Box dimensions [cm]	43,5cm x 29cm x 24cm

Technical data

LED module	Philips Fortimo DLM ES 2000/8xx G2 4K (Datasheet)
Light source wattage	17,5W
Luminaire wattage	17,5W
Lamp luminous flux	2050lm
Luminaire luminous flux	1625lm
Efficiency of the luminaire	92,9lm/W
ULOR	0%
Color temperature	4000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
L70TM-21 [wg LM-80]	>50 000h
LED photobiological threat	RG0 or RG1
Power Factor luminaire	PF > 0,9
THD factor	< 30%
Ta Rated temperature	+25°C
Ambient operating temp. range	-20...+45°C
This product contains light source of energy efficiency class D / EPREL	
Inrush current	3,01A/32,66µs
BUG rating	B1-U1-G0

Spare parts

06710000	Lampshade - service kit
46999752	LED module.

Files to download

Photometric LDT files	Photometric IES files
Manual	BIM Revit
BIM ArchiCAD	

Indexes

Index	Color	RAL
5004AL	ALUMINUM	9006
5004GR	GRAPHITE	7016

Other colors according to the "Colors Template" / RAL pattern book - available on request, subject to agreement with Norlys' Sales Department.

Norlys AS
P.B 1014 Hoff, 0218
Oslo
Hovfaret 4B, 0275
Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no

TÜVRheinland CERTIFIED — Management System ISO 9001:2015 IATF 16949:2016 — www.tuv.com ID 9108651873

PCC cert CERTIFICATE ISO 14001

RoHS 2011/65/UE

Before starting the assembly, you should read the instructions provided with the fixture. Due to the dynamic development of lighting technology, additional information is provided upon customer request. Condensation that may occur in the fixtures is a natural phenomenon and does not affect the quality of the fixture.