



### Type of luminaire

Type of luminaire	Wall light,
Photometric body	Double-sided light with 60° beam angle facing up and down.
Characteristics of the luminaire	Luminaire with a wide range of applications for example for illumination of walls and facade surfaces or any other architectural concepts.

### General information

Materials	Powder painted aluminum cast. Lens - safety glass, transparent. Silicone gasket. EPDM cable gland.
Mounting method	Fixing of the luminaire: 2 holes ø5mm, spacing 50x146mm.
Terminal	Connection terminals: max 3x2,5mm <sup>2</sup> , possibility to connect luminaire in loop max 3x1,5mm <sup>2</sup> . A round wire in the isolation with a diameter of max ø12mm.
Type of light source	LED module, electronic power supply
Light control	Non-dimmable fixture
Luminaire weight net	1,43kg
Box dimensions [cm]	20cm x 8,5cm x 10,5cm

### Technical data

2 LED modules	Yes
Light source wattage	6,4W
Luminaire wattage	7,2W
Lamp luminous flux	640lm
Color temperature	4000K
Colour rendering index CRI	80
L70B50 [wg LM-80]	>50 000h
Power Factor luminaire	PF 0,52
Ambient operating temp. range	Ta max=+65°C

Optional version, deadline, and terms of execution to be agreed with the Sales Department of Norlys Sp. z o.o.

BUG rating	B0-U3-G0
------------	----------

### Spare parts

46999373	LED module.
46999398	Power supply.

### Files to download

Photometric LDT files	Photometric IES files
3D models and drawings	Manual

### Indexes

Index	Color	RAL
5028AL	ALUMINUM	9006
5028BL	BLACK	9005
5028GR	GRAPHITE	7016
5028WH	WHITE	9003

Other colors according to the "Colors Template" pattern book - available on request, subject to agreement with Norlys' Sales Department.