

NORLYS HALDEN 5097


AC 220-240V 50-60Hz | IP 65 | IK 10 | LED | DALI2

Halden 5097XX0009
14.10.2026 v.09.17
www.norlys.no









Type of luminaire

Type of luminaire	Wall light,
Photometric body	Diffuse downward-directed hemispherical light
Characteristics of the luminaire	Luminaire with a wide range of applications for example for illumination of walls and facade surfaces or any other architectural concepts.

General information

Materials	Powder painted aluminum cast. Lens - transparent polycarbonate with structure, UV stabilized. Silicone gasket. EPDM cable gland.
Mounting method	Fixing of the luminaire: mounting plate with 2 adjust holes 7x10mm, spacing 100mm.
Terminal	Connection terminals: max 3x2,5mm², possibility to connect luminaire in max 3x1,5mm². A round wire in the isolation with a diameter of ø7...10,5mm.
Type of light source	LED module, DALI / TD electronic power supply Replaceable (LED only) light source by a professional. Replaceable control gear by a professional.
Light control	Light control in the system: DALI2/TD.
Luminaire weight net / gross	1,64kg / 1,94kg
Box dimensions [cm]	34cm x 17cm x 16,5cm
Luminaire dimensions [cm]	31cm x 15,5cm x 15cm

Technical data

LED module	Philips Fortimo SLM C 1203 L09 1619 G7 4K (Datasheet)
Driver	Yes
Driver durability	100000h
Light source wattage	6,7W
Luminaire wattage	8,8W
Lamp luminous flux	1121lm
Luminaire luminous flux	696lm
Efficiency of the luminaire	79,1lm/W
Color temperature	4000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
L70TM-21 [wg LM-80]	>50 000h
Power Factor luminaire	PF 0,85
Ta Rated temperature	+25°C
Ambient operating temp. range	-20...+45°C
This product contains light source of energy efficiency class D / EPREL	
Inrush current	5A / 220µs
BUG rating	B0-U1-G0

Spare parts

ZS5097zx0009	Repair kit.

Files to download

Photometric LDT files	Photometric IES files
Manual	

Indexes

Index	Color	RAL
5097AL	ALUMINUM	9006
5097GR	GRAPHITE	7016
5097WH	WHITE	9003

Other colors according to the "Colors Template" / RAL pattern book - available on request, subject to agreement with Norlys' Sales Department.

Norlys AS
P.B 1014 Hoff, 0218
Oslo
Hovfaret 4B, 0275
Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no

TÜVRheinland CERTIFIED — Management System ISO 9001:2015 IATF 16949:2016 — www.tuv.com ID 9108651873

PCC Cert CERTIFICATE ISO 14001

RoHS 2011/65/UE

Please read the manual before installing. Due to the dynamic development of lighting technology, additional information is available upon request. LED module must be replaced by a qualified person in accordance with applicable regulations. Condensation, which can occur in luminaires, is a natural phenomenon and does not impair the quality of the luminaire.