
NORLYS BODEN 5109

Boden 5109XX0010
14.10.2026 v.10.4
www.norlys.no





Type of luminaire

Type of luminaire	Wall light,
Photometric body	Diffused light.
Characteristics of the luminaire	A ceiling-type luminaire with a contemporary design

General information

Materials	Powder painted aluminum cast. Front - hot-dip galvanized steel or aluminum cast powder painted. Lens - milky polycarbonate, UV stabilized. Silicone gasket.
Mounting method	Mounting of the luminaire: 2 holes ø4,5mm, spacing 90x160mm
Terminal	Connection terminals: max 3x2,5mm² Possibility to connect the luminaire in loops, max 3x1,5mm² Round insulated cable with a diameter of ø7...10,5mm
Type of light source	LED module AC integrated Replaceable (LED only) light source by a professional.
Light control	Phase-dimming (TRIAC) TRAILING EDGE (TE) - LEADING EDGE (LE)
Luminaire weight net / gross	1,57kg / 1,74kg
Box dimensions [cm]	35,5cm x 17cm x 12cm

Technical data

LED module	Lumens EDC 57C 8W xxx 230V F201 4K (Datasheet)
External control	Phase dimmer Lumens LED AC (User manual)
Light source wattage	8W
Luminaire wattage	8W
Lamp luminous flux	772lm
ULOR	19%
Color temperature	4000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
Power Factor luminaire	PF 0,95
THD factor	30%
Ta Rated temperature	+25°C
Ambient operating temp. range	-20...+45°C

This product contains light source of energy efficiency class E / EPREL

Optionally, the luminaire is also available:
- For the LED color 2700K [1/1]
- For a different color of the fitting (according to the RAL color palette)

Terms of sale and other information, after contact with the Sales Department of Norlys.

Inrush current	35mA / 60ms

Spare parts

ZS5109zx0010	Repair kit.

Files to download

Manual

Indexes

Index	Color	RAL
5109BL	BLACK	9005
5109GA	HOT-DIP GALVANIZING	-

Other colors according to the "Colors Template" / RAL pattern book - available on request, subject to agreement with Norlys' Sales Department.

Norlys AS
P.B 1014 Hoff, 0218
Oslo
Hovfaret 4B, 0275
Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no

TÜVRheinland CERTIFIED
Management System ISO 9001:2015 IATF 16949:2016
www.tuv.com ID 9108651873

PCC Cert CERTIFICATE ISO 14001

RoHS 2011/65/UE

Before the installation, read the instructions attached to the luminaire. Installation and service work is carried out by a person with appropriate authorizations and qualifications, in accordance with applicable regulations. Due to the dynamic development of lighting technology, we provide additional information at the client's request. Condensation, which may occur in luminaires, is a natural phenomenon and does not deteriorate the quality of the luminaire.