


NORLYS ASKER POLE PRO 5164


AC 220-240V 50-60Hz | IP 65 | IK 06 | LED | No Dim

Asker pole pro
5164XX0010
02.11.2026 v.10.8
www.norlys.no









Type of luminaire

Type of luminaire	Pole luminaire (light construction).
Photometric body	Lens from Ledil type VSM (IESNA type V)
Characteristics of the luminaire	For the illumination of private areas, parks, and other architectural concepts.

General information

Materials	Extruded aluminum profile, powder coated. The outer hermetic lens - transparent PMMA plastic Silicone gasket.
Mounting method	Fixture mounting: 4 holes ø12mm, spacing 200x200mm. According to the included installation instructions. Other accessories must be purchased separately.
Terminal	Connection terminals: max 3x4mm², possibility of connecting the fixture in a loop max 3x4mm² Cable in a round sheath with a diameter: ø4...8mm, ø8...12mm, or ø10...13.6mm
Type of light source	Optical kit with IP67 (LED module and lens); electronic power supply Replaceable (LED only) light source by a professional. Replaceable control gear by a professional.
Light control	Non-dimmable fixture
Luminaire weight net / gross	11kg / 17,05kg
Box dimensions [cm]	26cm x 240cm x 53cm
Luminaire dimensions [cm]	236cm x 11cm x 39cm
Side area of luminaire	0,258m²

Technical data

LED module	Philips Fortimo FastFlex LED 2x6 DP G5 4K (Datasheet)
Driver	Yes
Driver durability	50000h
Light source wattage	6,1W
Luminaire wattage	8 W
Luminaire luminous flux	1186lm
Efficiency of the luminaire	148,3lm/W
ULOR	0,85%
Color temperature	4000K
Colour consistency (McAdam ellipse)	SDCM5
Flicker of light (Pst LM)	≤1
Strobe effect (SVM)	≤0.4
Colour rendering index CRI	70
L90B10 [wg LM-80]	100 000h
Power Factor luminaire	PF 0,86
THD factor	< 15%
Ta Rated temperature	+25°C
Ambient operating temp. range	-20...+45°C

This product contains light source of energy efficiency class D / EPREL

Inrush current	5A / 50µs
BUG rating	"B1-U1-G1"

Maximum number of luminaires of this type per MCB:

B 10A: 31, B 16A: 50, C 10A: 52, C 16A: 85

Accessories sold separately

117GA0009	Ground anchor

Spare parts

ZS5164xx0010	Repair kit.

Files to download

Photometric LDT files	Photometric IES files
Manual	

Norlys AS
P.B 1014 Hoff, 0218
Oslo
Hovfaret 4B, 0275
Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no

TÜVRheinland CERTIFIED — Management System ISO 9001:2015 IATF 16949:2016 — www.tuv.com ID 9108651873

PCC Cert CERTIFICATE ISO 14001

RoHS 2011/65/UE

ASKER POLE PRO 5164



Indexes

Index	Color	RAL
5164AL	ALUMINUM	9006
5164BL	BLACK	9005
5164GR	GRAPHITE	7016

Other colors according to the "Colors Template" / RAL pattern book - available on request, subject to agreement with Norlys' Sales Department.

Norlys AS
P.B 1014 Hoff, 0218
Oslo
Hovfaret 4B, 0275
Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no

Management System ISO 9001:2015 IATF 16949:2016
TÜVRheinland CERTIFIED
www.tuv.com ID 9108651873
PCC Cert CERTIFICATE ISO 14001
RoHS 2011/65/UE