

NORLYS KISA HEAD 5176


IP 65 | IK 08 | LED | DALI2

Kisa HEAD
5176XX0009
22.09.2026 v.09.6
www.norlys.no









Type of luminaire

Type of luminaire	Pole luminaire.
Photometric body	Double-sided diffused light.
Characteristics of the luminaire	A fixture with contemporary design. For lighting gardens and other private areas and public spaces.

General information

Materials	Extruded aluminum profile, powder coated. Lens - satin PMMA plastic.
Mounting method	According to the included assembly instructions. The remaining accessories must be purchased separately.
Terminal	IP68 sealed junction box, connection terminals: max 5x4mm², possibility of connecting a fixture in a loop max 5x2.5mm². Cable in a round sheath with a diameter of ø8...12.5mm.
Type of light source	LED module, electronic power supply Replaceable (LED only) light source by a professional. Replaceable control gear by a professional.
Light control	System light control: DALI outdoor full programm. The power supply is programmed for the maximum permitted current. Programming of other parameters after contact with the Norlys Sales Department.
Luminaire weight net / gross	5,9kg / 6,3kg
Box dimensions [cm]	16cm x 16cm x 93cm
Luminaire dimensions [cm]	14cm x 14cm x 90cm

Technical data

6 LED modules	Philips Fortimo Strip 0,5ft MF FC LV6 3K (Datasheet)
Driver	Yes
Driver durability	100000h
External control	DALI2 / NightDim (XI FP NLD) (User manual)
Light source wattage	23,5W
Luminaire wattage	27W
Lamp luminous flux	3891lm
Luminaire luminous flux	2432lm
Efficiency of the luminaire	90,1lm/W
ULOR	50%
Color temperature	3000K
Colour consistency (McAdam ellipse)	SDCM3
Flicker of light (Pst LM)	≤0.1
Strobe effect (SVM)	≤0.1
Colour rendering index CRI	80
L80B20 [wg LM-80]	>72 000h
L90B10 [wg LM-80]	>64 000h
Power Factor luminaire	PF 0,99
Overvoltage	6 / 10kV
Ta Rated temperature	25°C
Ambient operating temp. range	-20...+45°C

This product contains light sources of energy efficiency class D / EPREL

Optionally available fixture also:
- for LED color temperature of 2700K [1/1]
- for a different luminous flux value
- in a version with a surge protection device (SPD)
- for a different fixture color (according to the RAL color palette)

Terms of sale and other information upon agreement with the Sales Department of Norlys.

Inrush current	15A / 295µs
BUG rating	B1-U4-G1

Maximum number of luminaires of this type per MCB:

B 10A: 18, B 16A: 29, C 10A: 30, C 16A: 49

Spare parts

ZS5180zx0010	Service set.

Norlys AS
P.B 1014 Hoff, 0218
Oslo
Hovfaret 4B, 0275
Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no

TÜVRheinland CERTIFIED — Management System ISO 9001:2015 IATF 16949:2016 — www.tuv.com ID 9108651873

PCC Cert CERTIFICATE ISO 14001

RoHS 2011/65/UE

Before starting the installation, you should read the manual attached to the fixture. Installation and maintenance work should be carried out by a person with the appropriate authorizations and qualifications, in accordance with applicable regulations. Due to the dynamic development of lighting technology, additional information is provided at the customer's request. Condensation that may occur in fixtures is a natural phenomenon and does not affect the quality of the fixture.

KISA HEAD 5176

Files to download

Photometric LDT files	Photometric IES files
Manual	

Indexes

Index	Color	RAL
5176AL	ALUMINUM	9006
5176GR	GRAPHITE	7016

Other colors according to the "Colors Template" / RAL pattern book - available on request, subject to agreement with Norlys' Sales Department.

Norlys AS
P.B 1014 Hoff, 0218
Oslo
Hovfaret 4B, 0275
Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no

Before starting the installation, you should read the manual attached to the fixture. Installation and maintenance work should be carried out by a person with the appropriate authorizations and qualifications, in accordance with applicable regulations. Due to the dynamic development of lighting technology, additional information is provided at the customer's request. Condensation that may occur in fixtures is a natural phenomenon and does not affect the quality of the fixture.