



Type of luminaire

Type of luminaire	Wall light,
Photometric body	Diffused light, covered from the top.
Characteristics of the luminaire	Luminaire with stable and durable construction. For use in private and public areas requiring high resistance to external mechanical damage.

General information

Materials	Powder painted aluminum cast. Lens - milky polycarbonate, UV stabilized. Silicone gasket. EPDM cable gland.
Mounting method	Fixing of the luminaire: 4 oval holes 10x7, on a diameter of ø283mm every 90°, moved to the left from the vertical by 25°.
Terminal	Connection terminals: max 3x2,5mm ² , possibility to connect luminaire in loop max 3x2,5mm ² . A round wire in the isolation with a diameter ø7...10,5mm.
Type of light source	LED module AC integrated Replaceable (LED only) light source by a professional.
Light control	Non-dimmable fixture
Net / gross weight of luminaire	4,95kg / 5,8kg
Box dimensions [cm]	32,5cm x 32,5cm x 23cm

Technical data

Luminaire wattage	17,5W
Luminaire luminous flux	604lm
Efficiency of the luminaire	34,5lm/W
Color temperature	3000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
Rated life time L70/B50 at 25°C	50 000h
Power Factor luminaire	PF >0,9
Ta Rated temperature	+25°C
Ambient temperature	Ta max=+65°C

This product contains light source of energy efficiency class **E**

Spare parts

0659000	Lampshade.
08590000	Gasket.
46999751	LED module.

Files to download

Photometric LDT files	Photometric IES files
Manual	

Indexes

Index	Color	RAL
596AL	ALUMINUM	9006
596GR	GRAPHITE	7016