
NORLYS VISBY 6015

AC 220-240V 50-60Hz | IP 65 | IK 05 | LED | No Dim





Type of luminaire

Type of luminaire	Pole luminaire.
Photometric body	Indirect light with rotationally symmetrical light distribution.
Characteristics of the luminaire	Pole top luminaire for installation on a lighting pole with Ø60mm mounting cap. The luminaire is sold without a hat.

General information

Materials	Powder painted aluminum cast. Lens - transparent plastic PMMA. Silicone gasket.
Mounting method	Fixing of the luminaire: fitting to Ø60mm pole. Accessories must be ordered separately.
Terminal	H05VV-F 3G1 cable, 4,5m long, for connection inside the lighting pole (in appropriately selected electrical installation box).
Type of light source	LED module AC integrated Replaceable (LED only) light source by a professional.
Light control	Non-dimmable fixture
Luminaire weight net / gross	5,3kg / 6,15kg
Box dimensions [cm]	53cm x 23,5cm x 23,5cm

Technical data

LED module	Philips Fortimo LED DLM ES 3000lm G2
Light source wattage	27W
Luminaire wattage	27W
Lamp luminous flux	2950lm
Luminaire luminous flux	1525lm
Efficiency of the luminaire	56,5lm/W
ULOR	1,53%
Color temperature	3000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
Power Factor luminaire	PF>0,90
Ta Rated temperature	+25°C
Ambient operating temp. range	-20...+45°C
This product contains light source of energy efficiency class	A G E
Inrush current	2,63A/47,27µs

Accessories sold separately

3070XX0009	Reduction
154XX0010	Mounting adapter
7660XX0009	Reduction

Spare parts

0905770101	Electrical service kit.

Files to download

Manual

Indexes

Index	Color	RAL
6015AL	ALUMINUM	9006
6015GR	GRAPHITE	7016

Other colors according to the "Colors Template" / RAL pattern book - available on request, subject to agreement with Norlys' Sales Department.

Norlys AS
P.B 1014 Hoff, 0218
Oslo
Hovfaret 4B, 0275
Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no

TÜVRheinland CERTIFIED
Management System ISO 9001:2015 IATF 16949:2016
www.tuv.com ID 9108651873

PCC cert CERTIFICATE ISO 14001

RoHS 2011/65/UE

Please read the manual before installing. Due to the dynamic development of lighting technology, additional information is available upon request. LED module must be replaced by a qualified person in accordance with applicable regulations. Condensation, which can occur in luminaires, is a natural phenomenon and does not impair the quality of the luminaire.