

NORLYS MOSS 6162


IP 65 | IK 06 | AC 220-240V 50-60Hz | LED | DIM

Moss 6162XX0009
16.09.2026 v.09.17
www.norlys.no









Type of luminaire

Type of luminaire	Wall/ceiling luminaire.
Photometric body	Symmetric light with 36D beam angle.
Characteristics of the luminaire	For lighting gardens, private areas, and other architectural concepts. Possibility of adjusting the direction of illumination also in the vertical plane.

General information

Materials	Powder painted aluminum cast. Lampshade - safety glass, transparent.
Mounting method	Mounting of the fixture: 2 oval holes 5x10mm spacing 40mm.
Terminal	Electric connector terminal block 316IR 3M ™ Scotchlok ™ for connecting two or three wires with a cross-section of 0.5 - 1.5mm2 without removing the insulation from the wires.,
Type of light source	LED module AC integrated Replaceable (LED only) light source by a professional.
Light control	Phase-dimming (TRIAC) TRAILING EDGE (TE) - LEADING EDGE (LE)
Luminaire weight net / gross	0,4kg / 0,5kg
Box dimensions [cm]	10cm x 10cm x 15cm
Luminaire dimensions [cm]	7,5cm x 8cm x 13cm

Technical data

LED module	Lumens EDC 38C 4W xxx 230V A101 4K (Datasheet)
External control	Phase dimmer Lumens LED AC (User manual)
Light source wattage	4W
Luminaire wattage	4,2W
Lamp luminous flux	466lm
Luminaire luminous flux	406lm
Efficiency of the luminaire	96,7lm/W
ULOR	100%
Color temperature	4000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
L70TM-21 [wg LM-80]	59 000h
LED photobiological threat	RG0 or RG1
Power Factor luminaire	PF>0,98
THD factor	<20%
Ta Rated temperature	+25°C
Ambient operating temp. range	-20...+45°C
This product contains light source of energy efficiency class E / EPREL	
Inrush current	17mA / 60ms
BUG rating	B1-U0-G0

Accessories sold separately

6434XX0009	Clamp
6435XX0009	Clamp
6436XX0009	Clamp
6729XX0009	Mounting adapter
145ZX0009	Connection box

Files to download

Photometric LDT files	Photometric IES files
Manual	

Indexes

Index	Color	RAL
6162BL	BLACK	9005

Other colors according to the "Colors Template" pattern book - available on request, subject to agreement with Norlys' Sales Department.

Norlys AS
P.B 1014 Hoff, 0218
Oslo
Hovfaret 4B, 0275
Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no

TÜVRheinland CERTIFIED — Management System ISO 9001:2015 IATF 16949:2016 — www.tuv.com ID 9108651873

PCC Cert CERTIFICATE ISO 14001

RoHS 2011/65/UE

Before starting the assembly, please read the instructions attached to the fixture.
Due to the dynamic development of lighting technology, additional information is provided upon customer request.
Replacement of the LED module is only possible by a professional service of Norlys company.
Condensation, which may occur in fixtures, is a natural phenomenon and does not affect the deterioration of the fixture quality.