

NORLYS NICE 777


AC 220-240V 50-60Hz | IP 65 | LED

Nice 777XX0012
16.09.2026 v.12.2
www.norlys.no









Type of luminaire

Type of luminaire	Pole luminaire.
Photometric body	Indirect symmetrical light.
Characteristics of the luminaire	Surface-mounted luminaire designed to be installed on a lighting pole with a mounting post of Ø60mm.

General information

Materials	Powder painted aluminum cast. Lens - safety glass, transparent. Silicone gasket.
Mounting method	Fixing of the luminaire: luminaire adjusted to ø60mm lighting pole.
Terminal	4.5 m of H05VV-F 3G1 cable, for connection inside the lighting pole (in an appropriately selected electrical installation box).
Type of light source	LED module, electronic power supply
Light control	Non-dimmable fixture
Luminaire weight net / gross	9,18kg / 11,75kg
Box dimensions [cm]	80cm x 62cm x 62cm
Side area of luminaire	0,1m^2

Technical data

LED module	Philips SLM C 830 1211 L19 2828 G7
Driver	Yes
Light source wattage	32W
Luminaire wattage	36,6W
Lamp luminous flux	5571lm
Luminaire luminous flux	3190lm
Efficiency of the luminaire	87,2lm/W
ULOR	6,84%
Color temperature	3000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
Power Factor luminaire	PF 0,97
Ta Rated temperature	+25°C
Ambient operating temp. range	-20...+45°C
This product contains light source of energy efficiency class	D
Inrush current	18A/250µs
BUG rating	B1-U3-G1

Maximum number of luminaires of this type per MCB:

B 10A: 21, B 16A: 34, C 10A: 35, C 16A: 57

Accessories sold separately

3070XX0009	Reduction
154XX0010	Mounting adapter
7665XX0009	Reduction

Spare parts

06770000	Lampshade - service kit
08770001	Gasket.
46999692	LED module.
46999754	Power supply.

Files to download

Photometric LDT files	Photometric IES files
Manual	

Norlys AS
P.B 1014 Hoff, 0218
Oslo
Hovfaret 4B, 0275
Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no

TÜVRheinland CERTIFIED — Management System ISO 9001:2015 IATF 16949:2016 — www.tuv.com ID 9108651873

PCC cert CERTIFICATE ISO 14001

RoHS 2011/65/UE

Please read the manual before installing. Due to the dynamic development of lighting technology, additional information is available upon request. LED module must be replaced by a qualified person in accordance with applicable regulations. Condensation, which can occur in luminaires, is a natural phenomenon and does not impair the quality of the luminaire.

Indexes

Index	Color	RAL
777AL	ALUMINUM	9006

Other colors according to the "Colors Template" pattern book - available on request, subject to agreement with Norlys' Sales Department.

Norlys AS
P.B 1014 Hoff, 0218
Oslo
Hovfaret 4B, 0275
Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no

Management System ISO 9001:2015 IATF 16949:2016
www.tuv.com ID 9108651873

CERTIFICATE ISO 14001

RoHS 2011/65/UE

Please read the manual before installing. Due to the dynamic development of lighting technology, additional information is available upon request. LED module must be replaced by a qualified person in accordance with
applicable regulations. Condensation, which can occur in luminaires, is a natural phenomenon and does not
impair the quality of the luminaire.