
NORLYS CHELSEA 951

AC 220-240V 50-60Hz | IP 44 | E27

Chelsea 951XX0309
16.09.2026 v.09.3
www.norlys.no





Type of luminaire

Type of luminaire	Pole luminaire.
Photometric body	Light discovered
Characteristics of the luminaire	Classic design luminaire, mounted on a telescopic lighting pole. Adjustable height 2300..3200mm. For lighting gardens, terraces and other architectural concepts.

General information

Materials	Luminaire made of copper. Pole - aluminum cast powder painted, black color. Lens - clear polycarbonate, UV stabilized.
Mounting method	Fixing of the luminaire: 3 holes ø10,5mm, on a daimeter ø240mm every 120°. Set contains: art. 9012 - luminaire, art. 3010 - lightning pole, art. 9040- decorative arm. Other accessories must be ordered separately.
Terminal	Connection terminal: max. 4x2,5mm² cable, possibility to connect luminaire in loop max 4x2,5mm². A round wire in the isolation with a diameter of max ø7...12,5mm.
Type of light source	Lamp E27 A55...A60 Replaceable light source by an end-user.
Luminaire weight net / gross	11,28kg / 15,53kg
Side area of luminaire	0,112m²

Technical data

Lamp E27	A55..67
Light source wattage	LED MAX 11W
Luminaire wattage	LED MAX 11W
Ta Rated temperature	+25°C
Ambient operating temp. range	-20...+45°C

Accessories sold separately

7668ZX0009	Concrete foundation
305ZX0009	Concreting anchor
306ZX0009	Ground anchor
108GA0309	Adapter for concrete foundation

Files to download

Manual

Indexes

Index	Color	RAL
951CO	COPPER	-

Other colors according to the "Colors Template" pattern book - available on request, subject to agreement with Norlys' Sales Department.

Norlys AS
P.B 1014 Hoff, 0218
Oslo
Hovfaret 4B, 0275
Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no

TÜVRheinland CERTIFIED
Management System ISO 9001:2015 IATF 16949:2016
www.tuv.com ID 9108651873

PCC Cert CERTIFICATE ISO 14001

RoHS 2011/65/UE

Please read the manual before installing. Due to the dynamic development of lighting technology, additional information is available upon request. LED module must be replaced by a qualified person in accordance with applicable regulations. Condensation, which can occur in luminaires, is a natural phenomenon and does not impair the quality of the luminaire.