
NORLYS CHELSEA 957

AC 220-240V 50-60Hz | IP 44 | E27

Chelsea 957XX0309
16.09.2026 v.09.2
www.norlys.no





Type of luminaire

Type of luminaire	Post light fixture.
Photometric body	Light discovered
Characteristics of the luminaire	Classic design luminaire made of copper. For lighting gardens, terraces and other architectural concepts.

General information

Materials	Luminaire made of copper. Base - powder painted aluminum in black color. Lens - clear polycarbonate, UV stabilized.
Mounting method	Fixing of the luminaire: 2 holes ø5,5mm, spacing 90mm. For fixing on the ground, wall, platform and other construction. Set contains: art. 9012- luminaire, art. 9020- base of the luminaire. Other accessories need to be purchased separately.
Terminal	Connection terminals: max 2x2,5mm². Possibility to connect in loop max 2x1,5mm². A round wire in the isolation with a diameter of ø7...10,5mm.
Type of light source	Lamp E27 A55...A60
Luminaire weight net / gross	4,33kg / 7,13kg

Technical data

Lamp E27	A55..67
Light source wattage	LED MAX 11W
Luminaire wattage	LED MAX 11W
Ta Rated temperature	+25°C
Ambient operating temp. range	-20...+45°C

Accessories sold separately

307ZX0009	Concreting anchor

Files to download

Manual

Indexes

Index	Color	RAL
957CO	COPPER	-

Other colors according to the "Colors Template" pattern book - available on request, subject to agreement with Norlys' Sales Department.

Norlys AS
P.B 1014 Hoff, 0218
Oslo
Hovfaret 4B, 0275
Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no

TÜVRheinland CERTIFIED
Management System ISO 9001:2015 IATF 16949:2016
www.tuv.com ID 9108651873

PCC Cert CERTIFICATE ISO 14001

RoHS 2011/65/UE

Please read the manual before installing. Due to the dynamic development of lighting technology, additional information is available upon request. LED module must be replaced by a qualified person in accordance with
applicable regulations. Condensation, which can occur in luminaires, is a natural phenomenon and does not
impair the quality of the luminaire.